

Specification

Tyre Size	Rim Size	Weight ±2%	Dimension ±2%		Capacity / kg	
		(Kgs)	Diameter ±2%	Width ±2%	Speed 25 Km/h Max	
			(mm)	(mm)	Load Bearing	Steering
4.00-8	3.00-8	12	400	120	950	730
5.00-8	3.00-8	17	448	130	1415	1090
18x7-8(180/70-8)	4.33R-8	20	448	140	2145	1650
6.00-9	4.00E-9	26	522	153	1885	1450
21x8-9(200/75-9)	6.00E-9	34	518	190	2755	2120
6.50-10	5.00F-10	38	568	179	2340	1800
23x9-10(225/75-10)	6.50F-10	47	577	210	3445	2650
200/50-10	6.50F-10	24	450	196	2470	1900
7.00-12	5.00S-12	49	650	180	2920	2240
23x10-12	8.00G-12	48	576	232	3770	2900
27x10-12(250/75-12)	8.00G-12	70	662	234	3900	3000
7.00-15	5.5-15	54	720	175	3500	3200
7.50-15	6.5-15	70	744	210	3900	3000
28x9-15(8.15-15)	7.0-15	64	690	220	3445	2650
8.25-15	6.5-15	97	808	230	4750	3650
28x12.5-15	9.75-15	85	710	288	5040	3875
300-15(315/70-15)	8.0-15	105	815	255	5835	4450
355/65-15(350-15)	9.75-15	127	816	303	7800	6000
900-200	6.5-20	140	970	250	5340	4450
1000-20	7.5-20	175	1022	280	6000	5000

MEGASTAR®

Solid King

