



Robust Tread Design:

- Optimum contact area for better stability
- Excellent self-cleaning properties
- Minimum slippage and enhanced traction

Strong Nylon Carcass:

Safeguards the tyre against failures

Thick Under Tread:

Ensures protection from cuts and punctures



Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)		
		SW	OD					Speed, km/h (mph)		
		mm	mm				mm	mm	Bar	40
		in	in				in	in	Psi	25
10.5/80-18	W9	275	885	405	2647	12 PR 123 B	4.9	1630		
		10.8	34.8	15.9	104.2		72	3590		
400/70-20	13	404	1074	487	3212	16 PR 149 A8	4	3250		
		15.9	42.3	19.2	126.5		59	7160		
14.9-24	13	378	1241	565	3712	12 PR 145 A8	2.9	2900		
		14.8	48.8	22.2	146.1		43	6390		
16.9-24	15	429	1309	594	3915	12 PR 149 A8	2.6	3250		
		16.9	51.5	23.4	154.1		38	7160		
17.5L-24	15	445	1241	566	3712	10 PR 144 A8	2.2	2800		
		17.5	48.9	22.3	146.1		32	6170		
18.4-24	15	467	1375	621	4113	12 PR 155 A8	2.5	3875		
		18.4	54.1	24.4	161.9		37	8540		
18.4-26	16	467	1426	647	4265	12 PR 156 A8	2.5	4000		
		18.4	56.1	25.5	167.9		37	8810		
18.4-26	16	467	1426	647	4265	14 PR 159 A8	2.9	4375		
		18.4	56.1	25.5	167.9		43	9640		
16.9-28	15	429	1410	644	4218	12 PR 152 A8	2.6	3550		
		16.9	55.5	25.4	166.1		38	7820		
16.9-30	15	429	1461	670	4370	12 PR 153 A8	2.7	3650		
		16.9	57.5	26.4	172		40	8040		

BHB 310 – [R-4]



Backhoe
Loader



Size	Rim	Unloaded Dimensions		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)						Inflation Pressure	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							Speed, km/h (mph)							
								Drive Wheel							Free Wheel							
		mm	mm					Bar	Static	10	20	25	30		40	Bar	Static	10	20	25	30	40
		in	in							6	12	15	20		25			Psi	6	12	15	20
12.5/ 80-18	9	308	965	439	2887	12 PR	2.5	4260	2310	2020	1960	1920	1850	3.7	6100	3310	2890	2810	2760	2650		
						142 A8	36	9380	5090	4450	4320	4230	4070	54	13440	7290	6370	6190	6080	5840		
		12.1	38	17.3	113.7	14 PR	4	4600	2500	2180	2120	2080	2000	4	6670	3630	3160	3070	3020	2900		
						145 A8	62	10130	5510	4800	4670	4580	4410	62	14670	8000	6960	6760	6650	6390		
						132 A8																