



Unique XAD Pattern:

- Uniform wear
- Less slippage
- Improved fuel efficiency

Specially-designed CCR Compound:

Cut and chip-resistant compound provides excellent resistance to severe terrain conditions



Tyre Size	PR	TT/TL	Load Index/ Speed Symbol	Rim	Unloaded Inflation Dimension				Static Loaded Radius		Rolling Circumference		Max Speed		Load-carrying Capacity			
					SW		OD								Max Load		Inflation Pressure	
					mm	in	mm	in	mm	in	mm	in	kg	lbs	bar	psi		
16.9-24	14	TL	152A8	DW15L	429	16.9	1310	51.6	594	23.4	3934	154.9	40	25	3550	7820	3	44
17.5L-24	16	TL	153A8	DW15L	445	17.5	1241	48.9	565	22.2	3727	146.7	40	25	3650	8040	3.3	48
16.9-28	12	TT	152 A8	DW 15 L	429	16.9	1410	55.5	644	25.3	4217	166.0	40	25	3550	7820	2.6	38
16.9-28	14	TL	156 A8	DW 15L	429	16.9	1410	55.5	644	25.3	4217	166.0	40	25	4000	8820	3.2	47
18.4-26 IND	14	TT	159 A8	16	467	18.4	1450	57.1	656	25.8	4337	170.7	40	25	4375	9640	2.9	42

Tyre Size	PR	TT/TL	Load Index/ Speed Symbol	Rim	Unloaded Inflation Dimension				Static Loaded Radius		Rolling Circumference		Max Speed		Load-carrying Capacity			
					SW		OD								Max Load		Inflation Pressure	
					mm	in	mm	in	mm	in	mm	in	kg	lbs	bar	psi		
12.5/80-18	12	TT	142 A8/129A8	W9	308	12.1	965	38.0	438	17.2	2886	113.6	40	25	2650/1850	5840/4070	3.7	54
12.5/80-18	14	TL	145 A8/132A8	W9	308	12.1	965	38.0	438	17.2	2886	113.6	40	25	2900/2000	6390/4410	4.3	62