



Wider Lugs:

Easy to penetrate the soil, generate optimum traction and ensure comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Size	Rim	Unloaded Dimensions		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)							
								Field Operation			Speed, km/h(mph)				
		SW	OD	High Torque	Low Torque			Road Operation; Not high and sustained Torque							
		mm	mm		10			10	20	Static	10	12	30	40	
		in	in	Bar	6			6	12		6	20	20	25	
8.00-16	6LB	211	790	362	2363	6 PR 88 A8	1.9	600	840	690	1290	840	690	600	560
		8.3	31.1	14.3	93.0		27.55	1320	1850	1520	2890	1850	1520	1320	1230
8.3-20	W6	211	893	413	2671	6 PR 92 A8	2.4	670	950	770	1450	950	770	670	630
		8.3	35.2	16.3	105.2		34.8	1480	2090	1700	3190	2090	1700	1480	1390
9.5-20	W7	241	945	435	2817	6 PR 99 A8	2.1	830	1160	950	1780	1160	950	830	775
		9.5	37.2	17.1	111.3		30.45	1830	2560	2090	3920	2560	2090	1830	1710
11.2-20	W10	284	1002	458	2997	8 PR 107 A8	2.4	1040	1460	1200	2240	1460	1200	1040	975
		11.2	39.4	18.0	118.0		34.8	2290	3220	2640	4930	3220	2640	2290	2150
8.3-24	W7	211	993	463	2970	8 PR 105 A8	3.1	990	1390	1140	2130	1390	1140	990	925
		8.3	39.1	18.2	116.9		45.0	2180	3060	2510	4690	3060	2510	2180	2040
9.5-24	W8	241	1048	486	3135	8 PR 112 A8	2.8	1200	1680	1380	2580	1680	1380	1200	1120
		9.5	41.3	19.1	123.4		40.6	2640	3700	3040	5680	3700	3040	2640	2470
11.2-24	W10	284	1103	509	3299	8 PR 116 A8	2.5	1340	1880	1540	2880	1880	1540	1340	1250
		11.2	43.4	20.0	129.9		36.3	2950	4140	3390	6340	4140	3390	2950	2750
12.4-24	W11	315	1159	532	3467	8 PR 121 A8	2.2	1550	2180	1780	3340	2180	1780	1550	1450
		12.4	45.6	20.9	136.5		31.9	3410	4800	3920	7360	4800	3920	3410	3190
13.6-24	W12	345	1210	553	3619	8 PR 123 A8	1.9	1660	2330	1910	3570	2300	1910	1660	1550
		13.6	47.6	21.8	142.5		27.6	3660	5130	4210	7860	5130	4210	3660	3410
14.9-24	W13	378	1265	576	3784	8 PR 128 A8	1.8	1930	2700	2210	4140	2700	2210	1930	1800
							26.1	4250	5950	4870	9120	5950	4870	4250	3960
		14.9	49.8	22.7	149.0	12 PR 136 A8	2.6	2400	3060	2760	5150	3360	2760	2400	2240
							37.7	5290	7400	6080	11340	7400	6080	5290	4930
16.9-24	W15L	429	1333	604	3987	8 PR 133 A8	1.7	2200	3090	2530	4740	3090	2530	2200	2060
							23.9	4850	6810	5570	10440	6810	5570	4850	4540
		16.9	52.5	23.8	157.0	12 PR 143 A8	2.4	2920	4090	3350	6270	4090	3350	2920	2725
							34.8	6430	9010	7380	13810	9010	7380	6430	6000



Size	Rim	Unloaded Dimensions		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)							
								Field Operation			Speed, km/h(mph)				
		SW	OD	Road Operation; Not high and sustained Torque	Static			10	12	30	40	High Torque	Low Torque		
		mm	mm									10	10	20	
		in	in									in	in	in	in
Bar	10	10	20	Static	10	12	30	40							
Psi	6	6	12	Static	6	20	20	25							
14.9-26	W12	378	1316	601	3936	10 PR 129 A8	2.2	1980	2780	2280	4260	2780	2280	1980	1850
		15	51.80	23.60	154.9		32	4360	6120	5020	9380	6120	5020	4360	4070
16.9-26	W15L	429	1384	629	4140	10 PR 133 A8	1.9	2200	3090	2530	4740	3090	2530	2200	2060
		16.80	54.40	24.70	162.9		28	4850	6810	5570	10440	6810	5570	4850	4540
11.2-28	W10	284	1205	560	3604	8 PR 118 A8	2.5	1410	1980	1620	3040	1980	1620	1410	1320
		11.2	47.4	22.0	141.9		36.3	3110	4360	3570	6700	4360	3570	3110	2910
12.4-28	W11L	315	1260	582	3769	8 PR 123 A8	2.2	1660	2330	1910	3570	2330	1910	1660	1550
		12.4	49.6	22.9	148.4		31.9	3660	5130	4210	7860	5130	4210	3660	3410
13.6-28	W12	345	1311	604	3921	8 PR 125 A8	1.9	1770	2480	2030	3800	2480	2030	1770	1650
		13.6	51.6	23.8	154.4		27.6	3900	5460	4470	8370	5460	4470	3900	3630
14.9-28	W13	378	1367	627	4089	8 PR 130 A8	1.8	2030	2850	2340	4370	2850	2340	2030	1900
		14.9	53.8	24.7	161.0		26.1	4470	6280	5150	9630	6280	5150	4470	4190
16.9-28	W15L	429	1435	655	4292	8 PR 135 A8	1.7	2330	3270	2680	5010	3270	2680	2330	2180
							23.9	5130	7200	5900	11040	7200	5900	5130	4800
		16.9	56.5	25.8	169.0	12 PR 143 A8	2.4	2920	4090	3350	6270	4090	3350	2920	2725
							34.8	6430	9010	7380	13810	9010	7380	6430	6000
7.2-30	W6	183	1095	519	3275	6 PR 96 A8	2.8	760	1070	870	1630	1070	870	760	710
		7.2	43.1	20.4	128.9		41	1670	2360	1920	3590	2360	1920	1670	1560
9.5-30	W7	241	1200	562	3589	6 PR 111 A8	2.8	1170	1640	1340	2510	1640	1340	1170	1090
		9.4	47.2	22.1	141.2		41	2580	3610	2950	5530	3610	2950	2580	2400
14.9-30	W13	378	1418	652	4241	8 PR 127 A8	1.8	1870	2630	2150	4030	2630	2150	1870	1750
		14.8	55.8	25.6	166.9		26	4120	5790	4740	8880	5790	4740	4120	3850
16.9-30	W15L	429	1485	680	4442	8 PR 137 A8	1.65	2460	3450	2830	5290	3450	2830	2460	2300
							23.9	5420	7600	6230	11650	7600	6230	5420	5070
		16.9	58.5	26.8	174.9	12 PR 144 A8	2.5	3000	4200	3440	6440	4200	3440	3000	2800
							36.3	6610	9250	7580	141190	9250	7580	6610	6170
18.4-30	W16L	467	1552	707	4642	8 PR 139 A8	1.4	2600	3650	2990	5590	3650	2990	2600	2430
							20.3	5730	8040	6590	12310	8040	6590	5730	5350
		18.4	61.1	27.8	182.8	14 PR 152 A8	2.7	3800	5330	4370	8170	5330	4370	3800	3550
							39.0	8370	11740	9630	18000	11740	9630	8370	7820
8.3-32	W7	211	1195	565	3574	8 PR 107 A8	3.2	1170	1530	1310	2510	1530	1310	1090	975
		8.3	47	22.2	140.7		46.4	2580	3370	2890	5530	3370	2890	2580	2150
12.4-32	W11L	315	1362	633	4074	8 PR 125 A8	2.2	1770	2480	2030	3800	2480	2030	1770	1650
		12.4	53.6	24.9	160.4		31.9	3900	5460	4470	8370	5460	4470	3900	3630
9.5-32	W7	241	1251	587	3741	6 PR 106 A8	2.1	1020	1430	1170	2190	1430	1170	1020	950
		9.5	49.3	23.1	147.3		30.45	2250	3150	2580	4820	3150	2580	2250	2090



Size	Rim	Unloaded Dimensions		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)							
		SW	OD					Field Operation			Speed, km/h(mph)				
		mm	mm	10	Low Torque			Road Operation; Not high and sustained Torque							
		in	in		10			20	Static	10	12	30	40		
		mm	mm	Bar	6			6		12	Psi	6	20	20	25
16.9-34	W15L	429	1587	731	4747	8 PR 139 A8	1.7	2600	3650	2990	5590	3650	2990	2600	2430
		16.9	62.5	28.8	186.9		23.9	5730	8040	6590	12310	8040	6590	5730	5350
18.4-34	W16L	467	1654	758	4947	8 PR 142 A8	1.4	2840	3980	3260	6100	3980	3260	2840	2650
							20.3	6260	8770	7180	13440	8770	7180	6260	5840
		18.4	65.1	29.8	194.8	14 PR 153 A8	2.5	3910	5480	4490	8400	5480	4490	3910	3650
							36.25	8610	12070	9890	18500	12070	9890	8610	8040
12.4-36	W11L	315	1464	684	4379	8 PR 126 A8	2.2	1820	2550	2090	3910	2550	2090	1820	1700
		12.4	57.6	26.9	172.4		31.9	4010	5620	4600	8610	5620	4600	4010	3740
13.6-36	W12	345	1514	705	4529	8 PR 129 A8	1.9	1980	2780	2280	4260	2780	2280	1980	1850
		13.6	59.6	27.8	178.3		27.6	4360	6120	5020	9380	6120	5020	4360	4070
13.6-38	W12	345.0	1565.0	730.0	4681	8 PR 131 A8	2	2090	2930	2400	4490	2930	2400	2090	1950
		13.6	61.6	28.7	184.3		29	4600	6450	5290	9890	6450	5290	4600	4300
15.5-38	W14L	394	1569	732	4693	8 PR 133 A8	1.8	2200	3090	2530	4740	3090	2530	2200	2060
		15.5	61.8	28.8	184.8		26.1	4850	6810	5570	10440	6810	5570	4850	4540
16.9-38	W15L	429	1689	782	5052	8 PR 141 A8	1.7	2760	3860	3170	5920	3860	3170	2760	2575
		16.9	66.5	30.8	198.9		23.9	6080	8500	6980	13040	8500	6980	6080	5670
18.4-38	W16L	467	1755	809	5249	8 PR 143 A8	1.4	2920	4090	3350	6270	4090	3350	2920	2725
		18.4	69.1	32	206.7		20.3	6430	9010	7380	13810	9010	7380	6430	6000