

ULTRA LIGHT TRUCK



D96

D100

D102

D108

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE SINGLE	MAX. LOAD SINGLE	INFLATION PRESSURE DUAL	MAX. LOAD DUAL	RIM WIDTH
					OD (mm)	SW (mm)						
D96	145-10	6	76M	TL	505	147	6.5	50/345	400/880	-	-	3.5
		8	83M	TL	505	147	6.5	58/400	485/1070	-	-	3.5
D100	5.00-10	8	79/77L	TT	517	137	7.9	58/400	437/963	58/400	412/908	3.5
		10	83/81L	TL	517	137	7.9	62/425	487/1075	62/425	462/1020	3.5
D102	6.00-9	10	95L	TT	543	175	8.6	100/690	685/1510	-	-	4.5
	5.00-12	10	88/86L	TT	568	137	8.3	75/515	560/1230	75/515	530/1160	3.5
	6.00-13	10	99/97L	TT	653	166	8.7	72/500	780/1720	72/500	743/1640	4.5
	6.00-14	8	98/96L	TT	678	166	12.0	62/425	750/1650	62/425	710/1570	4.5
	6.50-14	8	102/100L	TT	702	175	11.0	62/425	840/1850	62/425	795/1750	4.5
		10	105/103L	TT	702	175	11.0	72/500	925/2040	72/500	875/1930	4.5
D108	7.50-14	8	102/100L	TT	755	206	9.4	62/425	840/1850	62/425	800/1765	6.0

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.