

# TRUCK AND BUS



**D103**

**D104**

**D106**

**D107**

**D108**

**D109**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
<b>D103</b>	8.25-20	14	136/132L	TT	974	236	14.0	115/790	2240/4940	105/720	2000/4410	6.5
	9.00-20	14	141/137L	TT	1019	259	13.5	110/760	2575/5675	100/690	2300/5070	7.0
		16	144/140L	TT	1019	259	13.5	125/860	2800/6175	115/790	2500/5510	7.0
<b>D104</b>	10.00-20	14	144/139L	TT	1054	278	13.9	100/690	2800/6175	90/620	2430/5355	7.5
		16	146/142L	TT	1054	278	13.9	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	11.5	115/790	3350/7390	105/720	2900/6395	8.0
<b>D106</b>	10.00-20	16	146/142L	TT	1054	278	13.4	115/790	3000/6610	105/720	2650/5840	7.5
	12.00-20	16	152/148L	TT	1125	315	12.0	105/720	3550/7830	95/660	3150/6940	8.5
		18	154/150L	TT	1125	315	12.0	115/790	3750/8270	105/720	3350/7390	8.5
<b>D107</b>	9.00-20	14	141/137L	TT	1019	259	14.4	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	15.4	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	16.8	115/790	3350/7390	105/720	2900/6395	8.0
<b>D108</b>	9.00-20	14	141/137L	TT	1019	259	14.9	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	15.4	115/790	3000/6610	105/720	2650/5840	7.5
	10.00-20	16HD*	146/142J	TT	1054	278	15.4	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	16.8	115/790	3350/7390	105/720	2900/6395	8.0
<b>D109</b>	10.00-20	16	146/142L	TT	1054	278	15.9	115/790	3000/6610	105/720	2650/5840	7.5

\*HD : Heavy Duty

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.