

LIGHT TRUCK



D102

D108

D112

D201

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE SINGLE	MAX. LOAD SINGLE	INFLATION PRESSURE DUAL	MAX. LOAD DUAL	RIM WIDTH
					OD (mm)	SW (mm)	mm	PSI/kPa	kgs/lbs	PSI/kPa	kgs/lbs	inch
D102	7.00-15	10	110/105L	TT	752	202	11.5	80/550	1060/2335	80/550	925/2040	5.5
		12	114/112L	TT	752	202	11.5	83/575	1180/2600	83/575	1120/2470	5.5
	7.50-15	12	120/118L	TT	780	211	12.0	87/600	1400/3085	87/600	1320/2910	6.0
		14	121/119L	TT	780	211	12.0	95/660	1450/3195	95/660	1360/3000	6.0
	6.50-16	12	111/106L	TT	755	182	12.0	95/660	1090/2400	95/660	950/2090	4.5
	7.00-16	12	116/114L	TT	776	194	12.0	83/575	1250/2755	83/575	1180/2600	5.5
		14	118/116L	TT	776	194	12.0	94/625	1320/2910	94/625	1250/2755	5.5
	7.50-16	12	121/119L	TT	808	220	12.0	87/600	1450/3195	87/600	1360/3000	6.0
		14	122/121L	TT	808	220	12.0	95/660	1500/3305	95/660	1450/3195	6.0
		14HD*	122/121G	TT	808	220	12.0	95/660	1500/3305	95/660	1450/3195	6.0
8.25-16	14	126/124L	TT	854	234	12.5	85/590	1700/3750	85/590	1600/3525	6.5	
D108	7.00-16	12	116/114L	TT	776	194	12.0	83/575	1250/2755	83/575	1180/2600	5.5
	7.50-16	12	121/119L	TT	808	220	12.3	87/600	1450/3195	87/600	1360/3000	6.0
		14HD*	122/121G	TT	808	220	12.3	95/660	1500/3305	95/660	1450/3195	6.0
	8.25-16	14	126/124L	TT	854	234	12.0	85/590	1700/3750	85/590	1600/3525	6.5
D112	9.00-16	8	199N	TL	860	274	9.0	45/310	1360/2995	-	-	8.0
D201	7.00-15	12	114/112L	TT	752	202	11.5	83/575	1180/2600	83/575	1120/2470	5.5
		12	120/118L	TT	780	211	12.0	87/600	1400/3085	87/600	1320/2910	6.0
	7.50-15	14	121/119L	TT	780	211	12.0	95/660	1450/3195	95/660	1360/3000	6.0
		16	123/121L	TT	780	211	12.0	110/760	1550/3415	110/760	1450/3195	6.0
	7.00-16	12	116/114L	TT	776	194	12.0	83/575	1250/2755	83/575	1180/2600	5.5
		14	118/116L	TT	776	194	12.0	94/650	1320/2910	94/650	1250/2755	5.5
	7.50-16	14	122/121L	TT	808	220	12.0	95/660	1500/3305	95/660	1450/3195	6.0
	8.25-16	14	126/124L	TT	854	234	12.5	85/590	1700/3750	85/590	1600/3525	6.5

*HD : Heavy Duty