

TRUCK AND BUS



D110

DSS111

D201

D202

D204

D205

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE SINGLE	MAX. LOAD SINGLE	INFLATION PRESSURE DUAL	MAX. LOAD DUAL	RIM WIDTH
					OD (mm)	SW (mm)	mm	PSI/kPa	kgs/lbs	PSI/kPa	kgs/lbs	inch
D110	10.00-20	16	146/142L	TT	1054	278	15.8	115/790	3000/6610	105/720	2650/5840	7.5
DSS111	10.00-20	16	146/142L	TT	1054	278	16.0	115/790	3000/6610	105/720	2650/5840	7.5
D201	9.00-20	14	141/137L	TT	1019	259	16.1	110/760	2575/5675	100/690	2300/5070	7.0
	10.00-20	16	146/142L	TT	1054	278	17.7	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	17.7	115/790	3350/7390	105/720	2900/6395	8.0
		18	152/147L	TT	1085	293	17.7	125/860	3550/7830	115/790	3075/6780	8.0
D202	12.00-20	18	154/150L	TT	1125	315	17.7	115/790	3750/8270	105/720	3350/7390	8.5
	8.25-20	14	136/132L	TT	982	236	15.0	115/790	2240/4940	105/720	2000/4410	6.5
		14	141/137L	TT	1019	259	17.7	110/760	2575/5675	100/690	2300/5070	7.0
D204	9.00-20	16	144/140L	TT	1019	259	17.7	125/860	2800/6175	115/790	2500/5510	7.0
	9.00-20	14	141/137L	TT	1019	259	15.0	110/760	2575/5675	100/690	2300/5070	7.0
D205	10.00-20	16	146/142L	TT	1054	278	19.7	115/790	3000/6610	105/720	2650/5840	7.5
	11.00-20	16	150/145L	TT	1085	293	17.7	115/790	3350/7390	105/720	2900/6395	8.0
		18	152/147L	TT	1085	293	17.3	125/860	3550/7830	115/790	3075/6780	8.0

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.