

TRUCK AND BUS



D206

D207

D208

D209

D325

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
D206	10.00-20	18	149/145L	TT	1067	278	21.6	130/900	3250/7160	120/830	2900/6395	7.5
D207	10.00-20	16	146/142L	TT	1073	278	22.6	115/790	3000/6610	105/720	2650/5840	7.5
		16 HD*	149/145J	TT	1073	278	22.6	115/790	3000/6610	105/720	2650/5840	7.5
		18	149/145L	TT	1073	278	22.6	130/900	3250/7160	120/830	2900/3695	7.5
		18 HD*	149/145L	TT	1073	278	22.6	130/900	3250/7160	120/830	2900/3695	7.5
	11.00-20	18	152/147L	TT	1140	293	24.0	125/860	3250/7160	115/790	3350/7830	8.0
		20	154/149L	TT	1140	293	24.0	130/900	3250/7160	120/830	3750/8270	8.0
D208	10.00-20	16	146/142L	TT	1073	278	21.1	115/790	3000/6610	105/720	2650/5840	7.5
D209	10.00-20	16	146/142L	TT	1067	278	21.1	115/790	3000/6610	105/720	2650/5840	7.5
		16 HD*	146/142J	TT	1067	278	21.1	115/790	3000/6610	105/720	2650/5840	7.5
		18	149/145L	TT	1067	278	21.1	130/900	3250/7160	120/830	2900/6395	7.5
		18 HD*	149/145J	TT	1067	278	21.1	130/900	3250/7160	120/830	2900/6395	7.5
D325	12.00-24	18	158/154G	TT	1275	315	36.0	115/790	4250/9370	105/720	3750/8270	8.5

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

*HD : Heavy Duty