

LAWN AND GARDEN

D265

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D265	4.00-4	2	29A3	TT	265	100	3.9	24/170	103/225	15/10	3.50
		4	43A3	TT	265	100	3.9	48/330	155/340	15/10	3.50
		6	51A3	TT	265	100	3.9	60/410	195/430	15/10	3.50
	4.10/3.50-4	2	29A3	TL	268	102	3.5	24/170	103/225	15/10	3.25
		4	43A3	TL	268	102	3.5	48/330	155/340	15/10	3.25
		2	29A3	TT	268	102	3.5	24/170	103/225	15/10	3.25
	4.80/4.00-8	4	43A3	TT	268	102	3.5	48/330	155/340	15/10	3.25
		2	29A3	TL	279	102	2.2	24/170	103/225	15/10	3.25
		4	43A3	TL	279	102	2.2	48/330	155/340	15/10	3.25
	11x4.00-5	2	26A3	TL	272	104	2.5	22/150	95/210	15/10	3.00
		4	42A3	TL	272	104	2.5	46/320	150/330	15/10	3.00
		2	38A3	TL	320	122	2.8	20/140	132/290	15/10	3.50
	13x5.00-6	4	52A3	TL	320	122	2.8	40/280	200/440	15/10	3.50
		2	41A3	TL	330	163	3.0	14/100	145/320	15/10	5.00
	13x6.50-6	4	55A3	TL	330	163	3.0	18/190	218/480	15/10	5.00
		2	45A3	TL	366	155	3.2	14/100	165/365	15/10	4.50
	15x6.00-6	4	61A3	TL	366	155	3.2	30/210	257/565	15/10	4.50
		4	66A3	TT	423	121	5.0	40/280	300/660	15/10	3.75
		6	78A3	TT	423	121	5.0	52/360	425/935	15/10	3.75
	4.80/4.00-8	2	52A3	TL	423	121	5.0	20/140	200/435	15/10	3.75
		4	66A3	TL	423	121	5.0	40/280	300/660	15/10	3.75
		6	78A3	TL	423	121	5.0	52/360	425/935	15/10	3.75
	16x6.50-8	4	64A3	TL	406	165	5.0	28/190	280/615	15/10	5.375
		2	55A3	TL	411	188	3.8	12/80	218/480	15/10	5.375
	16x7.50-8	4	69A3	TL	411	188	3.8	24/170	325/715	15/10	5.375
		8	83A3	TL	411	188	3.8	42/290	487/1070	15/10	5.375
		2	58A3	TL	457	163	4.8	14/100	236/520	15/10	5.00
	18x6.50-8	4	71A3	TL	457	163	4.8	28/190	345/760	15/10	5.00
2		58A3	TL	450	213	5.7	10/70	236/520	15/10	7.00	
18x8.50-8	4	74A3	TL	450	213	5.7	22/150	375/825	15/10	7.00	
	6	82A3	TL	450	213	5.7	34/230	475/1050	15/10	7.00	
	2	64A3	TL	462	235	5.7	10/70	280/615	15/10	7.00	
18x9.50-8	4	78A3	TL	462	235	5.7	20/140	425/935	15/10	7.00	
	2	63A3	TL	508	204	4.5	10/70	272/600	15/10	6.50	
20x8-8	4	79A3	TL	508	204	4.5	22/150	437/965	15/10	6.50	
	2	71A3	TL	508	254	6.2	10/70	345/760	15/10	8.00	
20x10.00-8	4	87A3	TL	508	254	6.2	22/150	545/1200	15/10	8.00	
	2	70A3	TL	508	254	5.3	10/70	335/740	15/10	8.00	
20x10-10	4	86A3	TL	508	254	5.3	22/150	530/1170	15/10	8.00	
	2	69A3	TL	574	213	5.2	10/70	325/715	15/10	7.00	
23x8.50-12	4	84A3	TL	574	213	5.2	22/150	500/1100	15/10	7.00	
	6	93A3	TL	574	213	5.2	34/230	650/1430	15/10	7.00	
	2	74A3	TL	577	235	5.5	10/70	375/825	15/10	7.00	
23x9.50-12	4	88A3	TL	577	235	5.5	22/150	560/1230	15/10	7.00	
	2	76A3	TL	579	264	6.0	10/70	400/880	15/10	8.50	
23x10.50-12	4	90A4	TL	579	264	6.0	20/140	600/1320	15/10	8.50	
	6	100A3	TL	579	264	6.0	32/220	800/1760	15/10	8.50	
24x12.00-12	4	99A3	TL	610	304	6.2	20/140	775/1710	15/10	9.50	
	2	87A3	TL	648	307	6.7	10/70	545/1200	15/10	10.50	
26x12.00-12	4	100A4	TL	648	307	6.7	20/140	800/1760	20/15	10.50	
	6	109A3	TL	648	307	6.7	30/210	1030/2270	15/10	10.50	
	8	117A4	TL	648	307	6.7	38/360	1250/2275	20/15	10.50	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

DEESTONE