

LAWN AND GARDEN

**D265T****D266****D267**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D265T	16x6.50-8	2	49A3	TL	406	165	2.8	14/100	185/410	15/10	5.375
D266	11x4.00-5	2	26A3	TL	272	104	2.5	22/150	95/210	15/10	3.00
		4	42A3	TL	272	104	2.5	46/320	150/330	15/10	3.00
	15x6.00-6	4	61A3	TL	366	155	3.2	30/210	257/565	15/10	4.50
	16x6.50-8	4	64A3	TL	406	165	3.7	28/190	280/620	15/10	5.375
		6	71A3	TL	406	165	3.7	46/330	375/825	15/10	5.375
	18x7.50-8	4	73A3	TL	457	191	4.8	24/170	365/805	15/10	6.00
	18x8.50-8	2	58A3	TL	450	213	4.3	10/70	236/520	15/10	7.00
		4	74A3	TL	450	213	4.3	22/150	375/825	15/10	7.00
	18x9.50-8	4	78A3	TL	462	235	6.2	20/140	425/935	15/10	7.00
	20x10.00-8	4	87A3	TL	508	254	6.2	22/150	545/1200	15/10	8.00
	20x10.00-10	4	86A3	TL	508	254	6.2	22/150	530/1170	15/10	8.00
		6	89A3	TL	508	254	6.2	34/230	580/1280	15/10	8.00
	23x10.50-12	4	90A4	TL	579	264	5.0	20/140	600/1320	20/15	8.50
		6	100A4	TL	579	264	5.0	32/220	800/1760	20/15	8.50
D267	22x11.00-8	4	94A3	TL	559	276	5.7	22/150	670/1480	15/10	8.50

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.