

# TRAILER



**D95**

**D268**

**D269**

**D292**

**D622**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
<b>D95</b>	4.80-8	6	71J	TT	423	121	4.7	90/620	345/760	-	-	3.75
		8	76E	TT	423	121	4.7	90/620	400/880	-	-	3.75
<b>D268</b>	16.5x6.50-8	4	64J	TL	411	165	3.9	45/310	280/615	-	-	5.375
		6	72J	TL	411	165	3.9	70/480	355/785	-	-	5.375
	18.5x8.50-8	4	71J	TL	462	213	5.5	35/250	345/760	-	-	7.0
		6	78J	TL	462	213	5.5	50/340	425/935	-	-	7.0
		12	90J	TL	462	213	5.5	92/630	600/1325	-	-	7.0
		4	77J	TL	518	203	6.2	35/250	412/910	-	-	6.0
	20.5x8.0-10	6	84J	TL	518	203	6.2	50/340	500/1100	-	-	6.0
		8	90J	TL	518	203	6.2	70/480	600/1320	-	-	6.0
10		95J	TL	518	203	6.2	90/620	690/1520	-	-	6.0	
12		99J	TL	518	203	6.2	110/760	775/1710	-	-	6.0	
<b>D269</b>	5.00-8	6	90F	TT	469	146	4.7	87/600	600/1320	-	-	4.0
		8	126F	TT	469	146	4.7	38/360	1700/3750	-	-	4.0
	6.00-9	8	126A2	TT	545	160	4.8	100/690	1700/3750	-	-	4.0
		10	134A2	TT	545	160	4.8	110/760	2120/4670	-	-	4.0
		12	143A2	TT	545	160	4.8	130/900	2725/6005	-	-	4.0
<b>D292</b>	7-14.5	8	102J	TL	677	185	5.5	70/480	850/1875	-	-	6.0
		12	110J	TL	677	185	5.5	100/690	1060/2335	-	-	6.0
		10	114J	TL	707	203	6.3	85/590	1180/2600	-	-	6.0
	8-14.5	12	117J	TL	707	203	6.3	100/690	1285/2835	-	-	6.0
		14	120J	TL	707	203	6.3	115/790	1400/3085	-	-	6.0
	205/75D14.5	10	114J	TL	707	203	6.3	85/590	1180/2600	-	-	6.0
14	120J	TL	707	203	6.3	115/790	1400/3085	-	-	6.0		
<b>D622</b>	ST165/80D13 (A78-13)	4	80/76L	TL	594	165	6.2	35/250	450/990	35/250	400/880	4.5
		6	88/83L	TL	594	165	6.2	50/350	560/1230	50/350	487/1070	4.5
	ST175/80D13 (B78-13)	4	84/79L	TL	610	177	7.6	35/250	500/1100	35/250	437/965	5.0
		6	91/87L	TL	610	177	7.6	50/350	615/1360	50/350	545/1200	5.0
	ST185/80D13 (C78-13)	4	87/82L	TL	626	184	7.0	35/250	545/1200	35/250	475/1050	5.0
		6	94/89L	TL	626	184	7.0	50/350	670/1480	50/350	580/1280	5.0
		8	99/95L	TL	626	184	7.0	65/450	775/1710	65/450	690/1520	5.0
		4	90/86L	TL	648	196	7.7	35/250	600/1320	35/250	530/1170	5.5
	ST195/75D14 (E78-14)	6	97/93L	TL	648	196	7.7	50/350	730/1610	50/350	650/1430	5.5
		8	102/98L	TL	648	196	7.7	65/450	850/1875	65/450	750/1655	5.5
	ST205/75D14 (F78-14)	4	93/89L	TL	664	203	7.8	35/250	650/1430	35/250	580/1280	5.5
		6	100/96L	TL	664	203	7.8	50/350	800/1760	50/350	710/1570	5.5
	ST205/75D15 (F78-15)	4	94/89L	TL	689	203	9.0	35/250	670/1480	35/250	580/1280	5.5
		6	101/97L	TL	689	203	9.0	50/350	825/1820	50/350	730/1610	5.5
ST225/75D15 (H78-15)	6	107/102L	TL	719	223	9.1	50/350	975/2150	50/350	850/1870	6.0	
	8	113/108L	TL	719	223	9.1	65/450	1150/2540	65/450	1000/2200	6.0	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

**DEESTONE**

© SUNLUN Group, all Rights Reserved  
For more information, please visit [www.sunlun.com.my](http://www.sunlun.com.my)

MOVE THE WORLD