

INDUSTRIAL IMPLEMENT



D256

D257

D289

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D256	4.10/3.50-4	2	32A3	TL	268	102	4.5	40/280	115/250	15/10	3.25
		2	32A3	TT	268	102	4.5	40/280	115/250	15/10	3.25
		4	47A3	TL	268	102	4.5	85/590	175/390	15/10	3.25
		4	47A3	TT	268	102	4.5	85/590	175/390	15/10	3.25
	4.80/4.00-8	2	57A3	TL	423	108	5.2	35/240	230/510	15/10	2.50
		4	80A3	TL	423	108	5.2	70/480	345/765	15/10	2.50
		6	-A3	TL	423	108	5.2	105/720	440/970	15/10	2.50
D257	3.00-4	2	29A3	TT	256	84	2.8	30/205	103/227	15/10	2.25
		4	52A3	TL	256	84	2.8	50/345	200/440	15/10	2.25
		4	52A3	TT	256	84	2.8	50/345	200/440	15/10	2.25
		6	64A3	TT	256	84	2.8	70/480	280/617	15/10	2.25
D289	4.10/3.50-4	2	32A3	TL	268	102	3.3	40/280	115/250	15/10	3.25
		2	32A3	TT	268	102	3.3	40/280	115/250	15/10	3.25
		4	47A3	TL	268	102	3.3	85/590	175/390	15/10	3.25
		4	47A3	TT	268	102	3.3	85/590	175/390	15/10	3.25
	4.80/4.00-8	2	57A3	TL	423	108	4.1	35/240	230/510	15/10	2.50
		4	71A3	TL	423	108	4.1	70/480	345/765	15/10	2.50