

FORKLIFT



D301

D333

PATTERN NAME	SIZE	PLY RATING	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD kgs/lbs		MAX. SPEED	RIM
				OD(mm)	SW(mm)	(mm)	PSI/kPa	LOAD WHEEL	STEERING WHEEL	KPH/MPH	Inch
D301	4.00-8	8	TT	414	115	13.9	130/896	-	670/1477	25/15	3.25
	5.00-8	8	TT	469	131	12.7	115/790	-	830/1830	25/15	3.00
	18x7-8	16	TT	465	168	13.4	145/1000	-	1640/3615	25/15	4.33
	21x8-6	14	TT	533	203	18.4	145/1000	2115/4660	1785/3940	25/15	6.00
	6.90/6.00-9	10	TT	545	160	14.2	125/860	1515/3340	1280/2820	25/15	4.00
	6.50-10	10	TT	597	178	15.8	115/790	1725/3805	1455/3210	25/15	5.00
		12	TT	597	178	15.8	140/970	1935/4260	1635/3600	25/15	5.00
	7.50-10	12	TT	647	203	18.2	120/830	2310/5090	1950/4300	25/15	5.50
	7.00-12	12	TT	683	192	18.2	125/860	2445/5395	2065/4555	25/15	5.00
		14	TT	683	192	18.2	145/1000	2670/5885	2255/4970	25/15	5.00
	250-15	18	TT	735	250	19.5	150/1030	4105/9050	3470/7650	25/15	7.50
	300-15	20	TT	840	300	20.7	135/930	5940/13100	4990/11000	25/15	8.00
	7.00-15	12	TT	762	203	18.2	125/860	2835/6245	2395/5275	25/15	6.00
		14	TT	762	203	18.2	145/1000	3090/6810	2610/5750	25/15	6.00
	7.00L-15	12	TT	731	199	18.2	125/860	2805/6185	2370/5220	25/15	5.50
	7.50-15 [30"]	12	TT	762	203	18.2	125/860	2835/6245	2395/5275	25/15	6.00
		14	TT	762	203	18.2	140/970	3505/7725	2965/6535	25/15	6.00
	7.50-15 [32"]	12	TT	808	215	18.2	115/790	3140/6920	2650/5845	25/15	6.00
8.15-15	12	TT	706	221	19.8	120/830	2810/6190	2370/5230	25/15	7.00	
	14	TT	706	221	19.8	140/970	3075/6775	2595/5720	25/15	7.00	
8.25-15	12	TT	847	236	18.2	105/720	3545/7810	2990/6595	25/15	6.50	
	14	TT	847	236	18.2	120/830	3830/8445	3235/7135	25/15	6.50	
D333	5.00-8	8	TT	469	131	18.0	115/790	- / -	830/1380	25/15	3.00
	6.00-9	10	TT	454	160	18.0	125/860	1515/3340	1280/2820	25/15	4.00
	6.50-10	10	TT	597	178	18.0	115/790	1725/3805	1455/3210	25/15	5.00
	7.00-12	12	TT	683	192	18.0	125/860	2445/5395	2065/4555	25/15	5.00
		14	TT	683	192	18.0	145/1000	2670/5885	2255/4970	25/15	5.00
	28x9-15	14	TT	706	221	20.0	140/970	3075/6775	2595/5720	25/15	7.00
300-15	20	TT	840	300	25.0	135/930	5940/13100	4990/11000	25/15	8.00	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

DEESTONE

© SUNLUN Group, all Rights Reserved
For more information, please visit www.sunlun.com.my

MOVE THE WORLD