

FORKLIFT



D306

D307

D308

PATTERN NAME	SIZE	PLY RATING	TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD (kgs/lbs)		MAX. SPEED (KPH/MPH)	RIM (Inch)
				OD(mm)	SW(mm)			LOAD WHEEL	STEERING WHEEL		
D306	5.00-8	8	TT	469	131	12.9	115/790	-	830/1830	25/15	3.00
	5.00-8 SOLID	-	Solid	458	143	23.0	-	1415/3120	1090/2405	25/15	3.25A
	6.00-9	10	TT	545	160	15.0	125/860	1515/3340	1280/2820	25/15	4.00
	6.00-9 SOLID	-	Solid	529	173	24.0	-	1885/4155	1450/3195	25/15	4.00E
	6.50-10	12	TT	597	178	15.3	140/970	1935/4260	1635/3600	25/15	5.00
	6.50-10 SOLID	-	Solid	576	191	25.5	-	2340/5160	1800/3970	25/15	5.00F
	7.00-12	14	TT	683	192	15.5	145/1000	2670/5885	2255/4970	25/15	5.00
		16	TT	638	192	15.5	155/1050	2830/6240	2320/5110	25/15	5.00
	7.00-12 SOLID	-	Solid	657	207	26.8	-	2920/6435	2240/4940	25/15	5.00S
	7.00-15	14	TT	762	203	15.4	145/1000	3090/6810	2610/5755	25/15	6.00
	7.50-15	14	TT	808	215	16.0	140/970	3505/7725	2965/6535	25/15	6.00
	8.15-15	12	TT	706	221	15.5	120/830	2810/6190	2370/5230	25/15	7.00
		14	TT	706	221	15.5	140/970	3075/6775	2595/5720	25/15	7.00
	8.25-15	12	TT	847	236	15.5	105/720	3545/7810	2990/6595	25/15	6.50
		14	TT	847	236	15.5	120/830	3830/8445	3235/7135	25/15	6.50
28x9-15 SOLID	-	Solid	700	221	23.0	-	3445/7595	2650/5842	25/15	7.00	
250-15 SOLID	-	Solid	720	225	24.0	-	4745/10460	3650/8046	25/15	7.00	
300-15 SOLID	-	Solid	815	250	24.0	-	5850/12897	4500/9920	25/15	8.00	
D307	5.00-8 SOLID	-	Solid	458	143	17.4	-	1415/3120	1090/2405	25/15	3.25A
	6.00-9 SOLID	-	Solid	529	173	19.0	-	1885/4155	1450/3195	25/15	4.00E
	6.50-10 SOLID	-	Solid	576	191	21.4	-	2340/5160	1800/3970	25/15	5.00F
	7.00-12 SOLID	-	Solid	657	207	21.4	-	2920/6435	2240/4940	25/15	5.00S
	28x9-15 SOLID	-	Solid	693	233	23.8	-	3445/7590	2650/5840	25/15	6.50
D308	4.00-8 SOLID	-	Solid	406	130	18.7	-	950/2095	730/1610	25/15	3.00D

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.