

DUMPER

**D203****D302****D303****D309****D403**

PATTERN NAME	SIZE	PLY RATING	LOAD INDEX		TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD (kgs/lbs)		MAX. SPEED (KPH/MPH)	RIM WIDTH (Inch)
			FREE ROLLING	DRIVE WHEEL		OD(mm)	SW(mm)			FREE ROLLING	DRIVE WHEEL		
D203	11.00-20	18	-	710A5	TT	1104	293	20.3	145/1000	-	6000/13225	25/15	8.00
D302	10.5/80-18	10	131	119	TT	885	274	21.5	53/370	1950/4300	1360/3000	40/25	9.00
		10	131	119	TL	885	274	21.5	53/370	1950/4300	1360/3000	40/25	9.00
	12.5/80-18	12	142	129	TT	965	308	21.5	53/370	2650/5840	1850/4080	40/25	9.00
		12	142	129	TL	965	308	21.5	53/370	2650/5840	1850/4080	40/25	9.00
		16	148	135	TL	965	308	21.5	71/490	3150/6940	2180/4805	40/25	9.00
D303	15.00/55-17 [380/55-17]	10	134	122	TL	850	391	24.9	38/260	2120/4670	1500/3305	40/25	13.00
		12	138	125	TL	850	391	24.9	40/280	2360/5200	1650/3635	40/25	13.00
	10.5/80-18EG	10	123	119	TL	885	274	22.0	53/370	1950/4300	1360/3000	40/25	9.00
		16	-	146	TL	885	274	22.0	85/585	4290/9455	3000/6610	40/25	9.00
	12.5/80-18EG	12	142	129	TT	965	308	26.8	53/370	2650/5840	1850/4080	40/25	9.00
		12	142	129	TL	965	308	26.8	53/370	2650/5840	1850/4080	40/25	9.00
	405/70-24	14	-	152	TL	1176	418	33.6	70/480	-	3550/7825	50/30	14.00
16.00/70-20EG [405/70-20]	14	154	142	TL	1075	418	30.1	51/350	3750/8265	2650/5840	40/25	14.00	
D309	10.00-20	16	-	164	TT	1075	278	15.3	130/900	-	5000/11020	25/15	7.50
D403	10.00/75-15.3	8	119	106	TT	760	264	20.1	45/310	1360/3000	950/2095	40/25	9.00
		8	119	106	TL	760	264	20.1	45/310	1360/3000	950/2095	40/25	9.00
		10	123	111	TL	760	264	20.1	57/400	1550/3415	1090/2400	40/25	9.00
	11.5/80-15.3	8	126	114	TT	845	290	22.0	39/270	1700/3745	1180/2600	40/25	9.00
		8	126	114	TL	845	290	22.0	39/270	1700/3745	1180/2600	40/25	9.00
		10	131	119	TL	845	290	22.0	49/340	1950/4300	1360/3000	40/25	9.00
	405/70-20	14	154	142	TL	1075	418	26.0	51/350	3750/8265	2650/5840	40/25	14.00