

# REAR FARM



**D317**

**D321**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
<b>D317</b>	12.4-24	8	117A8	TT	1159	315	30.7	32/220	1285/2830	40/25	11.00
<b>D321</b>	8.3-20	4	88A6	TT	890	211	42.5	24/160	560/1235	30/20	7.00
		6	96A6	TT	890	211	42.5	35/240	710/1560	30/20	7.00
	8.3-24	6	100A6	TT	995	211	39.0	35/240	800/1760	30/20	7.00
	9.5-24	6	106A6	TT	1048	241	37.0	30/210	950/2090	30/20	8.00
	11.2-24	6	106A8	TT	1103	284	48.0	26/180	950/2090	40/25	10.00
		8	113A8	TT	1103	284	48.0	36/250	1150/2540	40/25	10.00
	12.4-24	6	111A8	TT	1159	315	50.0	24/165	1090/2400	40/25	11.00
		8	117A8	TT	1159	315	50.0	32/220	1285/2830	40/25	11.00
13.6-26	6	116A8	TT	1260	345	50.0	22/150	1250/2760	40/25	12.00	
	8	121A8	TT	1260	345	50.0	28/190	1450/3200	40/25	12.00	