

SKID STEER


D316
D322
D323

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD (KGS/LBS)	MAX. SPEED (KPH/MPH)	RIM WIDTH (Inch)
					OD(mm)	SW(mm)					
D316	29x11.50-15	10	122A8	TL	730	270	17.0	65/450	1500/3300	40/25	10.00
	31x15.50-15	10	121B	TL	792	391	17.0	60/410	1450/3200	50/30	13.00
D322	10-16.5	8	-/A2	TL	773	264	30.0	60/410	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	30.0	75/520	2135/4710	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	34.5	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	34.5	80/550	2865/6320	10/5	9.75
D323	10-16.5	10	135A2	TL	773	264	35.0	60/415	2180/4806	10/5	8.25
	12-16.5	12	135	TL	831	307	35.0	65/44	2575/5677	10/5	9.75

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.