

FRONT FARM



D401(F-2)

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D401 (F-2)	3.50-6	2	19A6	TT	355	103	7.2	20/140	78/171	30/20	3.00
	3.50-6	4	33A6	TT	355	103	7.2	35/240	115/254	30/20	3.00
	4.00-6	2	20A6	TT	385	112	6.7	18/120	80/176	30/20	3.00
	3.50-8	2	25A6	TT	395	103	6.7	20/140	92.2/204	30/20	3.00
	3.50-8	4	37A6	TT	395	103	6.7	35/240	128/280	30/20	3.00
	4.00-8	2	30A6	TT	435	112	6.7	17/120	106/234	30/20	3.00
	4.00-8	4	43A6	TT	435	112	6.7	35/240	155/340	30/20	3.00
	4.00-10	4	48A6	TT	485	112	6.7	35/240	180/395	30/20	3.00
	4.00-12	4	56A8	TT	539	112	6.7	52/360	225/495	40/25	3.00
	5.60-13	6	68A8	TT	640	150	12.5	56/385	315/695	40/25	4.00
	5.00-15	4	69A8	TT	664	130	16.3	44/300	325/715	40/25	3.00
	5.00-15	6	75A8	TT	664	130	16.3	56/385	387/855	40/25	3.00
	5.50-16	6	82A8	TT	713	150	14.4	56/385	475/1050	40/25	4.00
	6.00-16	6	85A8	TT	739	159	20.1	52/360	515/1140	40/25	4.00
	6.50-16	6	88A8	TT	761	173	20.1	48/330	560/1230	40/25	4.50
	7.50-16	6	94A8	TT	808	203	23.5	44/300	670/1480	40/25	5.50
	7.50-16	8	99A8	TT	808	203	23.5	56/385	775/1710	40/25	5.50
	9.00-16	10	116A8	TT	855	234	24.0	56/390	1250/2755	40/25	6.00
	10.00-16	8	110A8	TT	894	274	27.0	44/300	1060/2340	40/25	8.00
	10.00-16	10	119A8	TT	894	274	27.0	50/340	1360/3000	40/25	8.00
11.00-16	8	114A8	TT	967	315	30.5	40/275	1180/2600	40/25	10.00	
11.00-16	10	122A8	TT	967	315	30.5	45/310	1500/3305	40/25	10.00	
7.50-18	8	102A8	TT	859	203	19.2	56/385	850/1870	40/25	5.50	
4.00-19	4	69A8	TT	717	112	10.5	52/360	325/715	40/25	3.00	
6.00-19	8	93A8	TT	814	165	22.0	48/330	690/1520	40/25	4.50	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.