

TRACTOR



D402A

D402B

D405A

| PATTERN NAME | SIZE | PLY RATING | LI/SS | TYPE | INFLATED DIMENSION | | TREAD DEPTH | INFLATION PRESSURE | MAX. LOAD | MAX. SPEED | RIM WIDTH |
|--------------|---------|------------|-------|------|--------------------|--------|-------------|--------------------|-----------|------------|-----------|
| | | | | | OD(mm) | SW(mm) | (mm) | PSI/kPa | KGS/LBS | KPH/MPH | Inch |
| D402A | 3.50-5 | 2 | 16A6 | TT | 330 | 103 | 10.6 | 20/140 | 71/157 | 30/20 | 3.00 |
| | | 4 | 31A6 | TT | 330 | 103 | 10.6 | 35/240 | 109/240 | 30/20 | 3.00 |
| | 3.50-6 | 2 | 19A6 | TT | 355 | 103 | 10.6 | 20/140 | 78/171 | 30/20 | 3.00 |
| | | 4 | 33A6 | TT | 355 | 103 | 10.6 | 35/240 | 115/254 | 30/20 | 3.00 |
| | 4.00-8 | 2 | 30A6 | TT | 435 | 112 | 11.5 | 18/120 | 106/234 | 30/20 | 3.00 |
| | | 4 | 43A6 | TL | 435 | 112 | 11.5 | 35/240 | 155/340 | 30/20 | 3.00 |
| | | 4 | 43A6 | TT | 435 | 112 | 11.5 | 35/240 | 155/340 | 30/20 | 3.00 |
| | 4.00-10 | 4 | 48A6 | TT | 485 | 112 | 11.5 | 35/240 | 180/395 | 30/20 | 3.00 |
| 4 | | 48A6 | TL | 485 | 112 | 11.5 | 35/240 | 180/395 | 30/20 | 3.00 | |
| D402B | 6.00-14 | 4 | 73A8 | TT | 674 | 167 | 14.0 | 36/250 | 365/800 | 40/25 | 4.00 |
| | | 6 | 81A8 | TT | 674 | 167 | 14.0 | 52/360 | 462/1020 | 40/25 | 4.00 |
| | 7.50-16 | 4 | 91A8 | TT | 805 | 205 | 23.0 | 29/200 | 615/1355 | 40/25 | 5.50 |
| | | 8 | 103A8 | TT | 805 | 205 | 23.0 | 54/370 | 875/1930 | 40/25 | 5.50 |
| D405A | 3.50-5 | 2 | 16A6 | TT | 330 | 103 | 8.7 | 20/140 | 71/157 | 30/20 | 3.00 |
| | | 4 | 31A6 | TT | 330 | 103 | 8.7 | 35/240 | 109/240 | 30/20 | 3.00 |
| | 3.50-6 | 2 | 19A6 | TT | 355 | 103 | 11.0 | 20/140 | 78/171 | 30/20 | 3.00 |
| | | 4 | 33A6 | TT | 355 | 103 | 11.0 | 35/240 | 115/254 | 30/20 | 3.00 |
| | 3.50-7 | 2 | 22A6 | TT | 370 | 103 | 11.0 | 20/140 | 85/187 | 30/20 | 3.00 |
| | | 4 | 35A6 | TT | 370 | 103 | 11.0 | 35/240 | 121/267 | 30/20 | 3.00 |
| | 4.00-8 | 2 | 30A6 | TT | 435 | 112 | 17.0 | 18/120 | 106/234 | 30/20 | 3.00 |
| | | 4 | 43A6 | TT | 435 | 112 | 17.0 | 35/240 | 155/340 | 30/20 | 3.00 |
| | 4.00-9 | 4 | 46A6 | TT | 460 | 112 | 17.0 | 35/240 | 170/375 | 30/20 | 3.00 |
| 4.00-10 | 4 | 48A6 | TT | 485 | 112 | 16.0 | 35/240 | 180/395 | 30/20 | 3.00 | |

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.