

AGRICULTURAL IMPLEMENT



D308(PG)

D315

D402B

D412

D8301

I-1

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD		MAX. SPEED (KPH/MPH)	RIM WIDTH (Inch)
					OD(mm)	SW(mm)			FREE ROLLING	DRIVE WHEEL		
D308	16.5/85-24	12	162/150A8	TT	1322	417	38.4	42/290	4750/10500	3350/7390	40/25	13.00
		12	162/150A8	TL	1322	417	38.4	42/290	4750/10500	3350/7390	40/25	13.00
	15.5/80-24	12	157/145A8	TL	1240	394	38.4	43/300	4125/9090	2900/6395	40/25	13.00
		12	157/145A8	TT	1240	394	38.4	43/300	4125/9090	2900/6395	40/25	13.00
		16	163/151A8	TL	1240	394	38.4	75/515	4875/10740	3450/7600	40/25	13.00
D315	11.5/80-15.3	14	139/126A8	TL	845	290	9.6	69/475	2430/5355	1700/3750	40/25	9.00
	12.5/80-15.3	14	142/129A8	TL	889	307	10.6	63/430	2650/5840	1850/4080	40/25	9.00
D402B	5.00-10	2	61/48A6	TT	510	135	17.0	18/124	257/565	180/395	30/20	3.50
		4	73/61A6	TT	510	135	17.0	33/225	365/805	275/565	30/20	3.50
D412	11L-15	10	118B	TL	777	279	12.5	44/300	1320/2910	-	50/30	8.00
		12	121B	TL	777	279	12.5	52/360	1450/3200	-	50/30	8.00
	11L-16	10	119B	TL	803	279	12.5	44/300	1360/3000	-	50/30	8.00
		12	122B	TL	803	279	12.5	52/360	1500/3300	-	50/30	8.00
D8301	10.00/75-15.3	10	123/111A8	TL	760	264	15.0	57/400	1550/3415	1900/2405	40/25	9.00
		12	126/114A8	TL	760	264	15.0	68/470	1700/3750	1180/2600	40/25	9.00
		14	130/118A8	TL	760	264	15.0	80/550	1900/4190	1320/2910	40/25	9.00
	11.5/80-15.3	14	139/126A8	TL	845	290	15.0	69/475	2430/5350	1700/3745	40/25	9.00
	12.00/75-18	10	135/123A8	TL	937	299	20.0	47/320	2180/4800	1550/3425	40/25	9.00
		12	139/126A8	TL	937	299	20.0	58/400	2430/5350	1700/3750	40/25	9.00
14		143/140A8	TL	937	299	20.0	72/500	2725/6000	1900/4190	40/25	9.00	
I-1	9.5L-15	10	116B	TL	767	241	7.0	52/360	1250/2760	-	50/30	7.00
	11L-15	10	118B	TL	777	279	7.0	44/300	1320/2910	-	50/30	8.00
	12.5L-15	12	127B	TL	823	318	7.0	52/360	1750/3860	-	50/30	10.00

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.