

# TRACTOR



## D405B

## D405C

## D407

## D408

## D413

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
<b>D405B</b>	23x8.50-12 SEG	4	84A4	TL	574	213	14.0	22/150	500/1100	20/15	7.00
		6	93A4	TL	574	213	14.0	34/230	650/1430	20/15	7.00
	23x10.50-12 SEG	4	90A4	TL	579	264	14.4	20/140	600/1320	20/15	8.50
		6	100A4	TL	579	264	14.4	32/220	800/1760	20/15	8.50
		10	118A3	TL	579	264	14.4	54/375	1320/2910	15/10	8.50
<b>D405C</b>	26x12.00-12 SEG	4	100A4	TL	648	307	18.0	20/140	800/1760	20/15	10.50
		6	104A3	TL	648	307	18.0	34/230	900/1985	15/10	10.50
<b>D407</b>	13x5.00-6	4	52A3	TL	320	122	7.7	40/280	200/440	15/10	3.50
	16x6.50-8	4	64A3	TL	406	165	9.6	28/190	280/615	15/10	5.375
<b>D408</b>	26x12.00-12	8	117A4	TL	648	307	18.4	48/330	1285/2835	20/15	10.50
		10	120A4	TL	648	307	18.4	60/415	1400/3085	20/15	10.50
<b>D413</b>	5-12	4	56A6	TT	528	127	23.0	34/235	224/495	30/20	4.00
	180/85D12	4	-/A6	TT	611	173	24.0	23/160	270/595	30/20	5.00
	7-14	4	72A6	TT	691	183	26.0	24/160	355/785	30/20	6.00
		6	80A6	TT	691	183	26.0	36/250	450/990	30/20	6.00
	7-16	4	75A6	TT	742	183	25.0	24/160	387/855	30/20	6.00
		6	84A6	TT	742	183	25.0	36/250	500/1100	30/20	6.00
	8-16	4	83A6	TT	790	211	26.8	18/125	487/1070	30/20	6.00
		6	91A6	TT	790	211	26.8	28/190	615/1360	30/20	6.00
	8-18	4	85A6	TT	841	211	26.8	18/125	515/1140	30/20	6.00
		6	94A6	TT	841	211	26.8	28/190	670/1480	30/20	6.00

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

**DEESTONE**

© SUNLUN Group, all Rights Reserved  
For more information, please visit [www.sunlun.com.my](http://www.sunlun.com.my)

MOVE THE WORLD