

ULTRA LIGHT TRUCK



D201

D206

D502

D504

| PATTERN NAME | SIZE | PLY RATING | LI/SS | TYPE | INFLATED DIMENSION | | TREAD DEPTH | INFLATION PRESSURE SINGLE | MAX. LOAD SINGLE | INFLATION PRESSURE DUAL | MAX. LOAD DUAL | RIM WIDTH |
|--------------|--------------|------------|----------|------|--------------------|---------|-------------|---------------------------|------------------|-------------------------|----------------|-----------|
| | | | | | OD (mm) | SW (mm) | mm | PSI/kPa | kgs/lbs | PSI/kPa | kgs/lbs | inch |
| D201 | 6.00-13 | 10 | 99/98L | TT | 653 | 166 | 9.0 | 72/500 | 780/1720 | 72/500 | 743/1640 | 4.5 |
| | 6.00-14 | 8 | 98/96L | TT | 678 | 166 | 9.0 | 62/425 | 750/1655 | 62/425 | 710/1565 | 4.5 |
| | 6.50-14 | 8 | 102/100L | TT | 702 | 175 | 11.9 | 62/425 | 840/1850 | 62/425 | 795/1750 | 4.5 |
| | | 10 | 105/103L | TT | 702 | 175 | 11.9 | 72/500 | 925/2040 | 72/500 | 875/1930 | 4.5 |
| D206 | 5.00-12 | 12 | 94/92L | TT | 568 | 137 | 9.5 | 88/585 | 670/1480 | 85/585 | 630/1390 | 3.5 |
| D502 | 6.40/6.50-13 | 6 | 85L | TT | 633 | 169 | 12.9 | 36/250 | 515/1135 | - | - | 5.0 |
| | | 8 | 90L | TT | 633 | 169 | 12.9 | 47/325 | 600/1320 | - | - | 5.0 |
| D504 | 5.00-12 | 10 | 88/86L | TT | 568 | 137 | 9.3 | 75/515 | 560/1230 | 75/515 | 530/1160 | 3.5 |
| | | 12 | 94/92L | TT | 568 | 137 | 9.3 | 85/585 | 670/1480 | 85/585 | 630/1390 | 3.5 |

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.