

INDUSTRIAL IMPLEMENT



D603

D604

D605

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D603	2.50-4	2	14A3	TL	216	61	2.8	30/205	67/147	15/10	1.50
		2	14A3	TT	216	61	2.8	30/205	67/147	15/10	1.50
		4	28A3	TL	216	61	2.8	50/345	100/220	15/10	1.50
		4	28A3	TT	216	61	2.8	50/345	100/220	15/10	1.50
	3.00-4	2	29A3	TL	256	84	3.3	30/205	103/227	15/10	2.25
		2	29A3	TT	256	84	3.3	30/205	103/227	15/10	2.25
		4	52A3	TL	256	84	3.3	50/345	200/440	15/10	2.25
		4	52A3	TT	256	84	3.3	50/345	200/440	15/10	2.25
D604	4.10/3.50-5	2	-A3	TT	294	102	4.9	40/280	130/285	15/10	3.25
		4	52A3	TT	294	102	4.9	85/590	200/445	15/10	3.25
D605	4.10/3.50-6	2	41A3	TT	319	102	1.6	40/280	145/320	15/10	3.25
		4	-A3	TT	319	102	1.6	85/590	225/495	15/10	3.25

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.