

TRAILER



D8034

D901

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE SINGLE	MAX. LOAD SINGLE	INFLATION PRESSURE DUAL	MAX. LOAD DUAL	RIM WIDTH
					OD (mm)	SW (mm)	mm	PSI/kPa	kgs/lbs	PSI/kPa	kgs/lbs	inch
D8034	16.5x6.50-8	4	64J	TL	411	165	5.5	45/310	280/615	-	-	5.375
		6	72J	TL	411	165	5.5	70/480	355/785	-	-	5.375
	18.5x8.50-8	4	71J	TL	462	213	5.5	35/250	345/760	-	-	7.0
		6	78J	TL	462	213	5.5	50/340	425/935	-	-	7.0
	20.5x8.0-10	4	77J	TL	518	203	7.9	35/250	412/910	-	-	6.0
		6	84J	TL	518	203	7.9	50/340	500/1100	-	-	6.0
		8	90J	TL	518	203	7.9	70/480	600/1320	-	-	6.0
		10	95J	TL	518	203	7.9	90/620	690/1520	-	-	6.0
		12	99J	TL	518	203	7.9	110/760	775/1710	-	-	6.0
D901	4.80-8	4	62J	TL	423	121	5.5	60/410	265/585	-	-	3.75
		6	71J	TL	423	121	5.5	90/620	345/760	-	-	3.75
	5.70-8	4	69J	TL	469	146	6.3	50/340	325/715	-	-	4.5
		6	77J	TL	469	146	6.3	75/520	412/910	-	-	4.5
		8	83J	TL	469	146	6.3	100/690	487/1070	-	-	4.5
	5.00-10	4	69/67J	TL	517	137	8.7	35/250	325/715	35/240	307/676	3.5
		6	74/72J	TL	517	137	8.7	43/300	375/826	43/300	355/782	3.5
		8	79/77J	TL	517	137	8.7	58/400	437/963	58/400	412/908	3.5
	4.80-12	4	72J	TL	524	121	5.5	60/410	355/785	-	-	3.75
		6	80J	TL	524	121	5.5	90/620	450/990	-	-	3.75
	5.00-12	8	83/81J	TL	568	137	5.5	58/400	487/1075	58/400	462/1020	4.25
	5.30-12	4	75J	TL	548	135	5.5	55/380	387/855	-	-	4.25
		6	82J	TL	548	135	5.5	80/550	475/1050	-	-	4.25
		8	87J	TL	548	135	5.5	100/690	545/1200	-	-	4.25
	ST175/80D13 (B78-13)	4	84/79L	TL	610	177	7.9	35/250	500/1100	35/250	437/965	5.0
		6	91/87L	TL	610	177	7.9	50/350	615/1360	50/350	545/1200	5.0
	ST215/75D14 (G78-14)	4	95/90L	TL	678	216	8.7	35/250	690/1520	35/250	600/1320	6.0
		6	102/98L	TL	678	216	8.7	50/350	850/1875	50/350	750/1650	6.0
	ST225/75D15 (H78-15)	6	107/102L	TL	719	223	9.5	50/350	975/2150	50/350	850/1870	6.0
		8	113/108L	TL	719	223	9.5	65/450	1150/2540	65/450	1000/2200	6.0

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.