

# LIGHT TRUCK



**D506**

**D902**

**D903**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH mm	INFLATION PRESSURE SINGLE PSI/kPa	MAX. LOAD SINGLE kgs/lbs	INFLATION PRESSURE DUAL PSI/kPa	MAX. LOAD DUAL kgs/lbs	RIM WIDTH inch
					OD (mm)	SW (mm)						
<b>D506</b>	7.00-16	12	116/114L	TT	776	194	16.5	83/570	1250/2750	83/570	1180/2600	5.5
		12	121/119L	TT	819	220	15.5	87/600	1450/3190	87/600	1360/2990	6.0
	7.50-16	14	122/121L	TT	819	220	15.5	95/650	1500/3300	95/650	1450/3190	6.0
<b>D902</b>	7.00-14	6	89/85L	TT	680	186	8.5	50/345	595/1310	50/345	525/1160	5.5
		6	95/91L	TT	721	190	8.5	50/345	690/1520	50/345	615/1355	5.0
	7.00-15	6	99/95L	TL	752	202	9.1	45/310	775/1710	45/310	690/1520	5.5
		8	105/101L	TL	752	202	9.1	65/450	925/2040	65/450	825/1820	5.5
		10	110/105L	TL	752	202	9.1	75/520	1060/2335	75/520	925/2040	5.5
	ST205/90D15 (7.00-15)	14	118/115L	TL	752	220	9.1	105/720	1320/2910	105/720	1215/2680	5.5
	6.50-16	6	97/93L	TT	755	183	8.5	50/345	730/1610	50/345	650/1435	4.5
		8	112/107L	TL	808	220	9.4	65/450	1120/2470	65/450	975/2150	6.0
	7.50-16	10	116/112L	TL	808	220	9.4	75/520	1250/2755	75/520	1120/2470	6.0
		ST225/90D16 (7.50-16)	14	123/120L	TL	808	220	9.4	105/720	1550/3415	105/720	1400/3085
	8.00-16.5	10	110/105L	TL	720	203	10.8	75/520	1060/2335	75/520	925/2040	6.0
		8	111/106L	TL	748	222	10.8	65/450	1090/2405	65/450	950/2095	6.75
	8.75-16.5	10	115/111L	TL	748	222	10.8	80/550	1215/2680	80/550	1090/2405	6.75
8		117/112L	TL	776	241	11.3	65/450	1285/2835	65/450	1120/2740	6.75	
9.50-16.5	10	121/117L	TL	776	241	11.3	80/550	1450/3195	80/550	1285/2835	6.75	
	7.50-16	8	112/107L	TT	808	220	11.0	65/450	1120/2470	65/450	975/2150	6.0
<b>D903</b>		12	121/119L	TT	808	220	11.0	87/600	1450/3195	87/600	1360/3000	6.0

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.