

ATV


D928
D929

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D928	22x11.00-8	2	36F	TL	559	281	13.5	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	13.5	5/35	155/340	80/50	9.00
		6	48F	TL	559	281	13.5	7/45	180/395	80/50	9.00
D929	16x8.00-7	2	9F	TL	406	204	9.5	4/25	58/128	80/50	6.50
		4	16F	TL	406	204	9.5	5/35	71/157	80/50	6.50
	20x7.00-8	2	16F	TL	508	177	9.5	4/25	71/157	80/50	5.50
		4	23F	TL	508	177	9.5	5/35	87.5/195	80/50	5.50
	22x11.00-8	2	36F	TL	559	281	11.9	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	11.9	5/35	155/340	80/50	9.00
	25x12.00-9	2	44F	TL	635	304	13.5	4/25	160/355	80/50	9.50
		4	51F	TL	635	304	13.5	5/35	195/430	80/50	9.50

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.