

ATV



D930

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D930	16x6.50-8	2	5F	TL	406	166	9.6	4/25	51.5/114	80/50	5.50
		4	12F	TL	406	166	9.6	5/35	63/139	80/50	5.50
		6	17F	TL	406	166	9.6	7/45	73/161	80/50	5.50
	22x11.00-8	2	36F	TL	559	281	12.4	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	12.4	5/35	155/340	80/50	9.00
	22x11.00-9	2	36F	TL	559	281	12.4	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	12.4	5/35	155/340	80/50	9.00
	25x12.00-9	2	44F	TL	635	304	13.4	4/25	160/355	80/50	9.50
		4	51F	TL	635	304	13.4	5/35	195/430	80/50	9.50
	22x11.00-10	2	35F	TL	559	281	12.4	4/25	121/265	80/50	9.00
		4	42F	TL	559	281	12.4	5/35	150/330	80/50	9.00
	24x11.00-10	2	40F	TL	610	281	13.4	4/25	140/310	80/50	9.00
		4	47F	TL	610	281	13.4	5/35	175/385	80/50	9.00
	25x12.00-10	2	44F	TL	635	304	13.4	4/25	160/355	80/50	9.50
		4	51F	TL	635	304	13.4	5/35	195/430	80/50	9.50
	23x8.00-11	2	26F	TL	584	204	12.4	4/25	95/210	80/50	6.50
		4	33F	TL	584	204	12.4	5/35	115/255	80/50	6.50
	24x9.00-11	2	33F	TL	610	227	12.4	4/25	115/255	80/50	7.00
		4	40F	TL	610	227	12.4	5/35	140/310	80/50	7.00
	24x10.00-11	2	36F	TL	610	254	12.4	4/25	125/275	80/50	8.00
		4	43F	TL	610	254	12.4	5/35	155/340	80/50	8.00
	25x8.00-12	2	31F	TL	635	204	14.4	4/25	109/240	80/50	6.50
		4	38F	TL	635	204	14.4	5/35	132/290	80/50	6.50
	25x10.00-12	2	38F	TL	635	254	14.4	4/25	132/290	80/50	8.00
		4	45F	TL	635	254	14.4	5/35	165/365	80/50	8.00