

# ATV


**D932**
**D933**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
<b>D932</b>	22x11.00-9	6	48F	TL	559	281	21.1	7/45	180/395	80/50	9.00
	25x12.00-9	6	56F	TL	635	304	21.1	7/45	224/495	80/50	9.50
	22x11.00-10	6	47F	TL	559	281	21.1	7/45	175/385	80/50	9.00
	24x11.00-10	6	52F	TL	610	281	21.1	7/45	200/440	80/50	9.00
	25x12.00-10	6	56F	TL	635	304	21.1	7/45	224/495	80/50	9.50
	25x8-12	6	43F	TL	635	204	21.1	7/45	155/340	80/50	6.50
	25x10-12	6	50F	TL	635	254	21.1	7/45	190/420	80/50	8.00
	26x10.00-12	6	52F	TL	660	254	24.9	7/45	200/460	80/50	8.00
	26x12.00-12	6	58F	TL	660	304	24.9	7/45	236/520	80/50	9.50
	27x10.00-12	6	56F	TL	686	254	24.9	7/45	224/495	80/50	8.00
	27x12.00-12	6	60F	TL	686	304	24.9	7/45	250/550	80/50	9.50
	28x10.00-12	6	57F	TL	711	254	24.9	7/45	230/505	80/50	8.00
	28x12.00-12	6	61F	TL	711	304	24.9	7/45	257/565	80/50	9.50
	AT27x10-14	6	53F	TL	686	254	21.0	7/45	206/455	80/50	8.00
AT30x9-14	6	57F	TL	762	227	21.0	7/45	230/505	80/50	7.00	
<b>D933</b>	23x8-11	4	33F	TL	584	204	14.4	5/35	115/255	80/50	6.50
		6	38F	TL	584	204	14.4	7/45	132/290	80/50	6.50
	24x9-11	4	40F	TL	610	227	15.3	5/35	140/310	80/50	7.00
		6	45F	TL	610	227	15.3	7/45	165/365	80/50	7.00
	25x8-12	4	38F	TL	635	204	15.3	5/35	132/290	80/50	6.50
		6	43F	TL	635	204	15.3	7/45	155/340	80/50	6.50
	25x10-12	4	45F	TL	635	254	15.3	5/35	165/365	80/50	8.00
		6	50F	TL	635	254	15.3	7/45	190/420	80/50	8.00

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.