

ATV



D936

D942

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D936	22x11.00-8	6	48F	TL	559	281	15.3	7/45	180/395	80/50	9.00
	22x11.00-9	6	48F	TL	559	281	15.3	7/45	180/395	80/50	9.00
	25x12.00-9	6	56F	TL	635	304	15.3	7/45	224/495	80/50	9.50
	22x8.00-10	6	36F	TL	559	204	15.3	7/45	125/275	80/50	6.50
	22x11.00-10	6	47F	TL	559	281	15.3	7/45	175/385	80/50	9.00
	23x8.00-10	6	39F	TL	584	204	14.4	7/45	136/300	80/50	6.50
	23x10.00-10	6	46F	TL	584	254	14.4	7/45	170/375	80/50	8.00
	24x11.00-10	6	52F	TL	610	281	15.3	7/45	200/440	80/50	9.00
	25x12.00-10	6	56F	TL	635	304	15.3	7/45	224/495	80/50	9.50
	27x12.00-10	6	60F	TL	686	304	28.8	7/45	250/550	80/50	9.50
	23x8.00-11	6	38F	TL	584	204	15.3	7/45	132/290	80/50	6.50
	24x8.00-11	6	41F	TL	610	204	14.4	7/45	145/320	80/50	6.50
	24x9.00-11	6	45F	TL	610	227	15.3	7/45	165/265	80/50	7.00
	24x10.00-11	6	48F	TL	610	254	14.4	7/45	180/395	80/50	8.00
	25x8.00-11	6	44F	TL	635	204	15.3	7/45	160/355	80/50	6.50
	25x10.00-11	6	51F	TL	635	254	15.3	7/45	195/430	80/50	8.00
	25x8.00-12	6	43F	TL	635	204	15.3	7/45	155/340	80/50	6.50
	25x10.00-12	6	50F	TL	635	254	15.3	7/45	190/420	80/50	8.00
	26x10.00-12	6	52F	TL	660	254	28.8	7/45	200/460	80/50	8.00
	26x12.00-12	6	58F	TL	660	304	28.8	7/45	236/520	80/50	9.50
27x10.00-12	6	54F	TL	686	254	28.8	7/45	212/467	80/50	8.00	
27x12.00-12	6	60F	TL	686	304	28.8	7/45	250/550	80/50	9.50	
28x10.00-12	6	56F	TL	711	254	28.8	7/45	224/495	80/50	8.00	
28x12.00-12	6	63F	TL	711	304	28.8	7/45	272/599	80/50	8.00	
D942	AT26x10.00R12	8	52F	T/L	660	254	19.1	7/48	200/440	80/50	8.00
	AT26x12.00R12	8	58F	T/L	660	304	19.1	7/48	236/520	80/50	9.50
	AT27x9.00R12	8	52F	T/L	686	227	19.1	7/48	200/440	80/50	7.00
	AT25x8.00R12	8	43F	T/L	635	204	19.1	7/48	190/440	80/50	6.50
	AT25x10.00R12	8	50F	T/L	635	254	19.1	7/48	200/440	80/50	8.00
	AT26x9.00R12	8	49F	T/L	660	227	19.1	7/48	185/410	80/50	7.00
	AT27x10.00R12	8	55F	T/L	686	236	19.5	7/48	220/485	80/50	7.00
	AT27x12.00R12	8	60F	T/L	686	304	19.1	7/48	250/550	80/50	9.50
	AT28x9.00R12	8	79F	T/L	711	226	19.1	7/48	433/955	80/50	7.00
	AT28x10.00R12	8	84F	T/L	711	264	19.1	7/48	495/1090	80/50	8.00
	AT26x9.00R14	8	48F	T/L	660	227	19.1	7/48	185/410	80/50	7.00
	AT26x11.00R14	8	54F	T/L	660	281	19.1	7/48	212/465	80/50	9.00

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

DEESTONE