

ATV


D943
D944
D985

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D943	AT22.5x10.00-8	6	45F	T/L	572	254	12.7	7/50	165/365	80/50	8.00
	AT22x12.00-8	6	51F	T/L	528	269	12.7	7/50	195/430	80/50	7.00
	AT25x13.00-9	6	59F	T/L	620	320	12.7	7/50	243/535	80/50	10.00
	AT20x10.00-10	4	68F	T/L	511	259	12.7	22/150	315/695	80/50	8.00
	AT22x9.50-10	4	71F	T/L	564	241	12.7	22/150	345/760	80/50	8.00
	AT22x11.00-10	4	77F	T/L	564	272	12.7	22/150	412/910	80/50	8.00
	AT23x11.00-10	4	79F	T/L	582	27	12.7	22/150	437/965	80/50	8.00
	AT24x9.50-10	4	76F	T/L	612	241	12.7	22/150	400/880	80/50	8.00
	AT24x10.50-10	4	81F	T/L	615	262	12.7	24/165	462/1020	80/50	8.00
	AT18x8.50-12	4	56F	T/L	457	198	12.7	22/150	224/495	80/50	7.00
	AT23x8.00-12	4	69F	T/L	584	198	12.7	24/165	325/715	80/50	6.00
	AT23x10.50-12	4	73F	T/L	579	264	12.7	20/140	365/800	80/50	8.50
	AT24x12.0012	4	81F	T/L	610	304	12.7	20/140	462/1020	80/50	9.50
	AT25x8.00-12	4	74F	T/L	635	203	12.7	24/165	375/8250	80/50	6.50
AT25x9.00-12	4	74F	T/L	635	227	12.7	20/140	375/825	80/50	7.00	
AT25x10.5-12	4	82F	T/L	635	264	12.7	24/165	475/1050	80/50	8.50	
D944	26x8.00-14	6	44F	T/L	660	204	20.0	7/45	160/355	80/50	6.50
	26x10.00-14	6	51F	T/L	660	254	20.0	7/45	195/430	80/50	8.00
	27x10.00-14	6	70J	T/L	686	254	20.0	12/40	335/740	100/60	8.00
	27x12.00-14	6	70J	T/L	686	305	20.0	12/40	335/740	100/60	9.50
D985	22.5x12.00-9	6	52F	T/L	572	304	24.3	7/45	200/240	80/50	9.50
	25x9.00-12	6	47F	T/L	635	227	24.3	7/45	175/385	80/50	7.00
	25x11.00-12	6	53F	T/L	635	281	24.3	7/45	206/455	80/50	9.00
	26x9.50-12	6	50F	T/L	660	241	24.3	7/45	190/420	80/50	8.00
	26x12.00-12	6	58F	T/L	660	304	24.3	7/45	236/520	80/50	9.50
	27x9.50-12	6	53F	T/L	686	241	24.3	7/45	206/455	80/50	8.00
	27x12.00-12	6	60F	T/L	686	304	24.3	7/45	250/550	80/50	9.50
	28x9.50-12	6	55F	T/L	711	241	24.3	7/45	218/480	80/50	8.00
28x12.00-12	6	63F	T/L	711	304	24.3	7/45	272/599	80/50	9.50	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.