



PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
HP100	35	295/35ZR21 XL	107	Y	-	BSW	10.5	10 - 11	736	296	7.8	975	2150	-	-	50	340	360	A	A
		315/35ZR20 XL	110	W	-	BSW	11.0	10.5 - 11.5	725	315	7.8	1060	2335	-	-	50	340	360	A	A
		285/35ZR22 XL	106	W	-	BSW	10.0	9.5 - 10.5	756	286	7.8	950	2095	-	-	50	340	360	A	A
	40	275/40ZR20 XL	106	Y	-	BSW	9.5	9 - 10	725	274	7.8	950	2095	-	-	50	340	360	A	A
		255/45R20 XL	105	V	-	BSW	8.5	8 - 9	734	251	7.8	925	2040	-	-	50	340	360	A	A
	45	275/45ZR19 XL	108	W	-	BSW	9.0	8.5 - 9.5	727	269	7.8	1000	2205	-	-	50	340	360	A	A
		275/45R20 XL	110	V	-	BSW	9.0	8.5 - 9.5	752	269	7.8	1060	2335	-	-	50	340	360	A	A
		285/45ZR19 XL	111	V	-	BSW	9.5	9 - 10	736	281	7.8	1090	2405	-	-	50	340	360	A	A
	55	215/55R18 XL	99	V	-	BSW	7.0	6.5 - 7.5	690	223	7.8	775	1710	-	-	50	340	360	A	A
		235/55ZR18 XL	104	W	-	BSW	7.5	7 - 8	712	241	7.8	900	1985	-	-	50	340	360	A	A
	60	215/60R16 XL	99	V	-	BSW	6.5	6 - 7	660	218	7.8	775	1710	-	-	50	340	360	A	A
		215/60R17 XL	100	V	-	BSW	6.5	6 - 7	686	218	8.0	800	1765	-	-	50	340	360	A	A
235/60R18 XL		107	V	-	BSW	7.0	6.5 - 7.5	735	236	8.0	975	2150	-	-	50	340	360	A	A	
65	215/65R16 XL	102	V	-	BSW	6.5	6 - 7	681	218	7.8	850	1875	-	-	50	340	360	A	A	
R200	80	155R12C	88/86	R	8	BSW	4.5	4.0 - 5.0	550	157	7.6	560	1235	530	1170	65	450	-	-	-
HT603	50	265/50R20 XL	112	V	-	BSW	8.5	8.0-9.0	774	277	8.5	1120	2470	-	-	50	340	560	A	A
		285/50R20	112	V	-	BSW	9.0	8.5-9.5	794	297	8.5	1120	2470	-	-	44	300	560	A	A
	235/55R18 XL	104	V	-	BSW	7.5	7.0-8.0	715	245	8.5	900	1985	-	-	50	340	560	A	A	
	55	255/55R18 XL	109	V	-	BSW	8.0	7.5-8.5	737	265	8.5	1030	2270	-	-	50	340	560	A	A
		275/55R20 XL	117	V	-	BSW	8.5	8.0-9.0	810	284	8.5	1285	2835	-	-	50	340	560	A	A
	60	265/60R18	110	H	-	BSW	8.0	7.5-8.5	775	272	8.5	1060	2335	-	-	44	300	560	A	A
	65	225/65R17	102	H	-	BSW	6.5	6.0-7.0	724	228	8.5	850	1875	-	-	44	300	560	A	A
		245/65R17 XL	111	H	-	BSW	7.0	6.5-7.5	750	248	8.5	1090	2405	-	-	50	340	560	A	A
		235/65R17 XL	108	H	-	BSW	7.0	6.5-7.5	738	240	8.5	1000	2205	-	-	50	340	560	A	A
	70	265/65R17	112	H	-	BSW	8.0	7.5-8.5	776	272	8.5	1120	2470	-	-	44	300	560	A	A
		235/70R16	106	H	-	BSW	7.0	6.5-7.5	736	240	8.5	950	2095	-	-	44	300	560	A	A
		265/70R16	112	H	-	BSW	8.0	7.5-8.5	778	272	8.5	1120	2470	-	-	44	300	560	A	A
		245/70R16 XL	111	H	-	BSW	7.0	6.5-7.5	750	248	8.5	1090	2405	-	-	50	340	560	A	A
		245/70R17	110	H	-	BSW	7.0	6.5-7.5	776	248	8.5	1060	2335	-	-	44	300	560	A	A
		215/70R16	100	H	-	BSW	6.5	6.0-7.0	708	221	8.5	800	1765	-	-	44	300	560	A	A
		225/70R16	103	H	-	BSW	6.5	6.0-7.0	722	228	8.5	875	1930	-	-	44	300	560	A	A
		215/70R15	98	H	-	BSW	6.5	6.0-7.0	683	221	8.5	750	1655	-	-	44	300	560	A	A
		235/70R17 XL	111	H	-	BSW	7.0	6.5-7.5	762	240	8.5	1090	2405	-	-	50	340	560	A	A
		225/70R15	100	H	-	BSW	6.5	6.0-7.0	697	228	8.5	800	1765	-	-	44	300	560	A	A
	205/70R15	96	H	-	BSW	6.0	5.5-6.5	669	209	8.5	710	1565	-	-	44	300	560	A	A	
265/70R17	115	H	-	BSW	8.0	7.5-8.5	804	272	8.5	1215	2680	-	-	44	300	560	A	A		
75	265/75R16	116	T	-	BSW	7.5	7.0-8.0	804	267	8.5	1250	2755	-	-	44	300	560	A	A	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.