


KACHA R101
KACHA R102
ST RADIAL R501

| PATTERN NAME | SERIES | SIZES | LI | SS | PR | SIDE WALL | RIM WIDTH | | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | TREAD DEPTH (MM) | MAX. LOAD CAPACITY SINGLE | | MAX. LOAD CAPACITY DUAL | | INFLATION PRESSURE | | UTQG | | |
|--------------|--------|---------|---------|----|----|-----------|-----------------|-----------------|-----------------------|--------------------|------------------|---------------------------|-------|-------------------------|-------|--------------------|-------|--------|-------|-------|
| | | | | | | | STANDARD (INCH) | APPROVAL (INCH) | | | | (KG) | (LBS) | (KG) | (LBS) | (PSI) | (kPa) | TREAD. | TRAC. | TEMP. |
| R101 | 80 | 165R13C | 94/92 | R | 8 | BSW | 4.5 | 4.0 - 5.0 | 596 | 167 | 8.2 | 670 | 1480 | 630 | 1390 | 65 | 450 | - | - | - |
| | | 185R14C | 102/100 | Q | 8 | BSW | 5.5 | 5.0 - 6.0 | 650 | 188 | 8.6 | 850 | 1874 | 800 | 1764 | 65 | 450 | - | - | - |
| | | 195R14C | 106/104 | P | 8 | BSW/WSW | 5.5 | 5.0 - 6.0 | 666 | 198 | 9.0 | 950 | 2094 | 900 | 1984 | 65 | 450 | - | - | - |
| | | 195R15C | 106/104 | P | 8 | BSW | 5.5 | 5.0 - 6.0 | 690 | 198 | 9.0 | 950 | 2094 | 900 | 1984 | 65 | 450 | - | - | - |
| | | 205R14C | 109/107 | P | 8 | BSW | 6.0 | 5.5 - 6.5 | 686 | 208 | 9.0 | 1030 | 2270 | 975 | 2150 | 65 | 450 | - | - | - |
| | | 205R16C | 110/108 | R | 8 | BSW | 6.0 | 5.5 - 6.5 | 736 | 208 | 9.5 | 1060 | 2335 | 1000 | 2205 | 65 | 450 | - | - | - |
| R102 | 80 | 195R14 | 106/104 | R | 8 | BSW | 5.5 | 5.0 - 6.0 | 666 | 198 | 9.0 | 950 | 2095 | 900 | 1985 | 65 | 450 | - | - | - |

| PATTERN NAME | SERIES | SIZES | LOAD RANGE | PR | SIDE WALL | RIM WIDTH | | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | TREAD DEPTH (MM) | MAX. LOAD CAPACITY SINGLE | | MAX. LOAD CAPACITY DUAL | | INFLATION PRESSURE | | UTQG | | |
|--------------|--------|-------------|------------|----|-----------|-----------------|-----------------|-----------------------|--------------------|------------------|---------------------------|-------|-------------------------|-------|--------------------|-------|--------|-------|-------|
| | | | | | | STANDARD (INCH) | APPROVAL (INCH) | | | | (KG) | (LBS) | (KG) | (LBS) | (PSI) | (kPa) | TREAD. | TRAC. | TEMP. |
| R501 | 75 | ST205/75R14 | C | 6 | BSW | 5.5 | 5.0 - 6.0 | 664 | 203 | 7.2 | 800 | 1760 | 710 | 1570 | 50 | 350 | - | - | - |
| | | ST205/75R14 | D | 8 | BSW | 5.5 | 5.0 - 6.0 | 664 | 203 | 7.2 | 925 | 2040 | 825 | 1820 | 65 | 450 | - | - | - |
| | | ST205/75R15 | C | 6 | BSW | 5.5 | 5.0 - 6.0 | 689 | 203 | 7.2 | 825 | 1820 | 730 | 1610 | 50 | 350 | - | - | - |
| | | ST205/75R15 | D | 8 | BSW | 5.5 | 5.0 - 6.0 | 689 | 203 | 7.2 | 975 | 2150 | 850 | 1870 | 65 | 450 | - | - | - |
| | | ST215/75R14 | C | 6 | BSW | 6.0 | 5.5 - 6.5 | 678 | 216 | 7.2 | 850 | 1870 | 750 | 1650 | 50 | 350 | - | - | - |
| | | ST225/75R15 | D | 8 | BSW | 6.0 | 5.5 - 6.5 | 719 | 223 | 7.2 | 1150 | 2450 | 1000 | 2200 | 65 | 450 | - | - | - |
| | 80 | ST225/75R15 | E | 10 | BSW | 6.0 | 5.5 - 6.5 | 719 | 223 | 7.2 | 1285 | 2830 | 1120 | 2470 | 80 | 550 | - | - | - |
| | | ST235/80R16 | E | 10 | BSW | 6.5 | 6.0 - 7.0 | 782 | 235 | 7.8 | 1550 | 3420 | 1360 | 3000 | 80 | 550 | - | - | - |
| | | ST235/80R16 | F | 12 | BSW | 6.5 | 6.0 - 7.0 | 782 | 235 | 7.8 | 1650 | 3630 | 1450 | 3195 | 95 | 650 | - | - | - |
| | | ST175/80R13 | C | 6 | BSW | 5.0 | 4.5 - 5.5 | 610 | 177 | 7.0 | 615 | 1360 | 545 | 1200 | 50 | 350 | - | - | - |

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.