

NAKARA R201

NAKARA R202

PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R201	50	225/50R17	94	H	BSW	7.0	6.5 - 7.5	658	233	7.9	670	1480	44	300	500	A	A
	55	215/55R17	94	H	BSW	7.0	6.5 - 7.5	668	226	7.9	670	1480	44	300	500	A	A
		205/55R16	91	H	BSW	6.5	6.0 - 7.0	632	214	7.9	615	1355	44	300	500	A	A
	60	185/60R14	82	H	BSW	5.5	5.0 - 6.0	578	189	8.1	475	1047	44	300	500	A	A
		195/60R15	88	V	BSW	6.0	5.5 - 6.5	615	201	7.8	560	1234	44	300	500	A	A
		205/60R15	91	H	BSW	6.0	5.5 - 6.5	627	209	7.9	615	1355	44	300	500	A	A
		215/60R16	95	H	BSW	6.5	6.0 - 7.0	664	221	7.9	690	1520	44	300	500	A	A
		185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	7.9	500	1100	44	300	500	A	A
		215/60R15	94	H	BSW	6.5	6.0 - 7.0	639	221	7.9	670	1480	44	300	500	A	A
		225/60R15	96	H	BSW	6.5	6.0 - 7.0	651	228	7.9	710	1565	44	300	500	A	A
		205/60R16	92	H	BSW	6.0	5.5 - 6.5	652	209	7.9	630	1390	44	300	500	A	A
		225/60R16	98	H	BSW	6.5	6.0 - 7.0	676	228	7.9	750	1655	44	300	500	A	A
		235/60R16	100	H	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A
	195/60R14	86	T	BSW	6.0	5.5 - 6.5	590	201	7.9	530	1160	44	300	500	A	A	
	65	165/65R13	77	T	BSW	5.0	4.5 - 5.5	544	170	7.6	412	908	44	300	500	A	A
		175/65R14	82	H	BSW	5.0	4.5 - 5.5	584	177	7.8	475	1047	44	300	500	A	A
		185/65R14	86	H	BSW	5.5	5.0 - 6.0	596	189	7.8	530	1168	44	300	500	A	A
		185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	7.8	560	1234	44	300	500	A	A
		215/65R15	96	H	BSW	6.5	6.0 - 7.0	661	221	7.9	710	1565	44	300	500	A	A
		195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.9	615	1355	44	300	500	A	A
		205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.9	670	1480	44	300	500	A	A
		215/65R16 XL	102	H	BSW	6.5	6.0 - 7.0	686	221	7.9	850	1875	50	340	500	A	A
		205/65R16	95	H	BSW	6.0	5.5 - 6.5	672	209	7.9	690	1520	44	300	500	A	A
		235/65R16	103	T	BSW	7.0	6.5 - 7.5	712	240	7.9	875	1930	44	300	500	A	A
	215/65R17	99	T	BSW	6.5	6.0 - 7.0	712	221	7.9	775	1710	44	300	500	A	A	
	70	165/70R13	79	T	BSW	5.0	4.5 - 5.5	562	170	7.6	437	963	44	300	500	A	A
		175/70R13	82	T	BSW	5.0	4.5 - 5.5	576	177	8.1	475	1047	44	300	500	A	A
		175/70R14	84	H	BSW	5.0	4.5 - 5.5	602	177	7.8	500	1102	44	300	500	A	A
		185/70R13	86	H	BSW	5.5	5.0 - 6.0	590	189	7.8	530	1168	44	300	500	A	A
		185/70R14	88	H	BSW	5.5	5.0 - 6.0	616	189	7.8	560	1234	44	300	500	A	A
		195/70R14	91	H	BSW	6.0	5.5 - 6.5	630	201	8.1	615	1356	44	300	500	A	A
		205/70R14 XL	98	H	BSW	6.0	5.5 - 6.5	644	209	8.1	750	1655	50	340	500	A	A
215/70R15		98	H	BSW	6.5	6.0 - 7.0	683	221	8.1	750	1655	44	300	500	A	A	
80	155/80R12	77	T	BSW	4.5	4.0 - 5.0	553	157	7.9	412	910	44	300	500	A	A	
	165/80R15	87	T	BSW	4.5	4.0 - 5.0	645	165	7.9	545	1200	44	300	500	A	A	
R202	70	155/70R13	75	T	BSW	4.5	4.0 - 5.0	548	157	7.2	387	853	44	300	300	A	B
		155/70R12	73	T	BSW	4.5	4.0 - 5.0	523	157	6.9	365	805	44	300	240	A	A
	80	155/80R13	79	T	BSW	4.5	4.0 - 5.0	578	157	6.9	437	963	44	300	300	A	B
		165R13	82	S	BSW	4.5	4.0 - 5.0	594	165	7.6	475	1047	44	300	240	A	A

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.