



PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG			
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.	
R302	30	265/30ZR19 XL	93	W	BSW	9.5	9.0 - 10.0	643	271	7.9	650	1435	50	340	420	A	A	
	35	235/35ZR19 XL	91	W	BSW	8.5	8.0 - 9.0	647	241	7.9	615	1355	50	340	420	A	A	
	40	225/40ZR18 XL	92	W	BSW	8.0	7.5 - 8.5	637	230	7.9	630	1390	50	340	420	A	A	
		235/40ZR18 XL	95	W	BSW	8.5	8.0 - 9.0	645	241	7.9	690	1520	50	340	420	A	A	
	45	215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	7.9	545	1200	44	300	420	A	A	
		225/45ZR17 XL	94	W	BSW	7.5	7.0 - 8.0	634	225	7.9	670	1480	50	340	420	A	A	
	50	225/45ZR18 XL	95	W	BSW	7.5	7.0 - 8.0	659	225	7.9	690	1520	50	340	420	A	A	
		195/50R15	82	V	BSW	6.0	5.5 - 6.5	577	201	7.9	475	1050	44	300	500	A	A	
		205/50ZR17 XL	93	W	BSW	6.5	6.0 - 7.0	638	214	7.9	650	1435	50	340	420	A	A	
		215/50ZR17	91	W	BSW	7.0	6.5 - 7.5	648	226	7.9	615	1355	44	300	420	A	A	
		225/50ZR17	94	W	BSW	7.0	6.5 - 7.5	658	233	7.9	670	1480	44	300	420	A	A	
		225/50R16	92	V	BSW	7.0	6.5 - 7.5	632	233	7.9	630	1390	44	300	500	A	A	
		195/50R16 XL	88	V	BSW	6.0	5.5 - 6.5	602	201	7.9	560	1230	50	340	500	A	A	
	55	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	7.9	475	1050	44	300	500	A	A	
		185/55R16	83	V	BSW	6.0	5.5 - 6.5	610	194	7.9	487	1070	44	300	500	A	A	
		195/55R15	85	V	BSW	6.0	5.5 - 6.5	595	201	7.9	515	1140	44	300	500	A	A	
		195/55R16	87	V	BSW	6.0	5.5 - 6.5	620	201	7.9	545	1200	44	300	500	A	A	
		205/55R15	88	V	BSW	6.5	6.0 - 7.0	607	214	7.9	560	1230	44	300	500	A	A	
		205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	7.9	615	1355	44	300	500	A	A	
		215/55R16 XL	97	V	BSW	7.0	6.5 - 7.5	642	226	7.9	730	1610	50	340	500	A	A	
	60	215/55ZR17	94	W	BSW	7.0	6.5 - 7.5	668	226	7.9	670	1480	44	300	420	A	A	
		225/55R16 XL	99	V	BSW	7.0	6.5 - 7.5	654	233	7.9	775	1710	50	340	500	A	A	
		185/60R15	84	V	BSW	5.5	5.0 - 6.0	603	189	7.9	500	1100	44	300	500	A	A	
		195/60R15	88	V	BSW	6.0	5.5 - 6.5	615	201	7.9	560	1230	44	300	500	A	A	
		205/60R15	91	V	BSW	6.0	5.5 - 6.5	627	209	7.9	615	1355	44	300	500	A	A	
		205/60R16	92	V	BSW	6.0	5.5 - 6.5	652	209	7.9	630	1390	44	300	500	A	A	
		215/60R15	94	V	BSW	6.5	6.0 - 7.0	639	221	7.9	670	1480	44	300	500	A	A	
	65	215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	7.9	690	1520	44	300	500	A	A	
		225/60R15	96	V	BSW	6.5	6.0 - 7.0	651	228	7.9	710	1565	44	300	500	A	A	
		225/60R16	98	V	BSW	6.5	6.0 - 7.0	676	228	7.9	750	1655	44	300	500	A	A	
		235/60R16	100	V	BSW	7.0	6.5 - 7.5	688	240	7.9	800	1765	44	300	500	A	A	
		215/60R17	96	H	BSW	6.5	6.0 - 7.0	690	221	7.9	710	1565	44	300	500	A	A	
		195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	7.8	615	1355	44	300	500	A	A	
		205/65R15	94	H	BSW	6.0	5.5 - 6.5	647	209	7.9	670	1480	44	300	500	A	A	
	70	205/70R15	96	T	BSW	6.0	5.5 - 6.5	669	209	7.9	710	1565	44	300	500	A	A	
	80	155/80R13	79	H	BSW	4.5	4.0 - 5.0	578	157	7.9	437	965	44	300	500	A	A	
	RA01	45	215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	8	545	1200	44	300	500	A	A
			225/45ZR17	91	W	BSW	7.5	7.0 - 8.0	634	225	8	615	1355	44	300	500	A	A
			235/45ZR17 XL	97	W	BSW	8.0	7.5 - 8.5	644	236	8	730	1610	50	340	500	A	A
		50	245/45ZR17	95	W	BSW	8.0	7.5 - 8.5	652	243	8	690	1520	44	300	500	A	A
195/50R16			84	V	BSW	6.0	5.5 - 6.5	602	201	8	500	1100	44	300	500	A	A	
215/50ZR17			91	W	BSW	7.0	6.5 - 7.5	648	226	8	615	1355	44	300	500	A	A	
55		225/50ZR17 XL	98	W	BSW	7.0	6.5 - 7.5	658	233	8	750	1655	50	340	500	A	A	
		185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	8	475	1050	44	300	500	A	A	
		185/55R16	83	H	BSW	6.0	5.5 - 6.5	610	194	8	487	1070	44	300	500	A	A	
		195/55R15	85	V	BSW	6.0	5.5 - 6.5	595	201	8	515	1140	44	300	500	A	A	
		195/55R16	87	V	BSW	6.0	5.5 - 6.5	620	201	8	545	1200	44	300	500	A	A	
		205/55R16	91	V	BSW	6.5	6.0 - 7.0	632	214	8	615	1355	44	300	500	A	A	
		215/55R16	93	V	BSW	7.0	6.5 - 7.5	642	226	8	650	1435	44	300	500	A	A	
60		215/55ZR17	94	W	BSW	7.0	6.5 - 7.6	668	226	8	670	1480	44	300	500	A	A	
		185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	8	500	1100	44	300	500	A	A	
		195/60R15	88	V	BSW	6.0	5.5 - 6.5	615	201	8	560	1230	44	300	500	A	A	
		205/60R15	91	V	BSW	6.0	5.5 - 6.5	627	209	8	615	1355	44	300	500	A	A	
		205/60R16	92	V	BSW	6.0	5.5 - 6.5	652	209	8	630	1390	44	300	500	A	A	
		215/60R16	95	V	BSW	6.5	6.0 - 7.0	664	221	8	690	1520	44	300	500	A	A	
		225/60R16	98	V	BSW	6.5	6.0 - 7.5	676	228	8	750	1655	44	300	500	A	A	
65	185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	8	560	1230	44	300	500	A	A		
	195/65R15	91	H	BSW	6.0	5.5 - 6.5	635	201	8	615	1355	44	300	500	A	A		
	205/65R15	94	H	BSW	6.0	5.5 - 7.5	647	209	8	670	1480	44	300	500	A	A		
	205/65R16	95	V	BSW	6.0	5.5 - 7.5	672	209	8	690	1520	44	300	500	A	A		
		215/65R15 XL	100	H	BSW	6.5	6.0 - 7.0	661	221	8	800	1765	50	340	500	A	A	

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

