



PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R401	80	195R14C	106/104	P	8	BSW	5.5	5.0 - 6.0	666	198	9.0	950	2095	900	1985	65	450	-	-	-
R402	60	185/60R15C	94/92	T	6	BSW	5.5	5.0 - 6.0	603	197	9.4	670	1480	630	1390	54	375	-	-	-
		205/65R16C	107/105	R	8	BSW	6.0	5.5 - 6.5	672	209	9.1	975	2150	925	2040	69	475	-	-	-
	65	215/65R16C	109/107	R	8	BSW	6.5	6.0 - 7.0	686	221	9.4	1030	2270	975	2150	69	475	-	-	-
		235/65R16C	115/113	R	8	BSW	7.0	6.5 - 7.5	712	240	9.4	1215	2680	1150	2535	69	475	-	-	-
	70	195/70R15C	104/102	R	8	BSW	6.0	5.5 - 6.5	655	201	9.5	900	1985	850	1875	65	450	-	-	-
		205/70R15C	106/104	Q	8	BSW	6.0	5.5 - 6.5	669	209	9.5	950	2094	900	1984	65	450	-	-	-
		215/70R15C	109/107	R	8	BSW	6.5	6.0 - 7.0	683	221	9.5	1030	2270	975	2150	65	450	-	-	-
		225/70R15C	112/110	R	8	BSW	6.5	6.0 - 7.0	697	228	9.4	1120	2470	1060	2335	65	450	-	-	-
		255/70R15C	112/110	R	8	BSW	7.5	7.0 - 8.0	739	260	9.5	1120	2470	1060	2335	55	375	-	-	-
	75	195/75R16C	107/105	R	8	BSW	5.5	5.0 - 6.0	698	204	10.0	975	2150	925	2040	69	475	-	-	-
		205/75R16C	110/108	R	8	BSW	5.5	5.0 - 6.0	714	203	9.1	1060	2335	1000	2205	69	475	-	-	-
		215/75R16C	113/111	R	8	BSW	6.0	5.5 - 6.5	728	216	9.4	1150	2535	1090	2405	69	475	-	-	-
		225/75R16C	116/114	R	8	BSW	6.0	5.5 - 6.5	744	223	9.4	1250	2755	1180	2600	69	475	-	-	-
	R403	70	245/70R16	107	S	-	BSW	7.0	6.5 - 7.5	750	248	10.0	975	2149	-	-	44	300	-	-
225/70R15C			109/107	S	6	BSW	6.5	6.0 - 7.0	697	228	9.8	1030	2270	975	2150	55	375	-	-	-

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
T88	65	215/65R16C	109/107	R	8	BSW	6.5	6.0 - 7.0	686	221	8.5	1030	2270	975	2150	69	475	-	-	-
	70	205/70R15C	106/104	S	8	BSW	6.0	5.5 - 6.5	669	209	8.5	950	2094	900	1984	65	450	-	-	-
		215/70R15C	109/107	R	8	BSW	6.5	6.0 - 7.0	683	221	8.5	1030	2270	975	2150	65	450	-	-	-

Source : Deestone
 Disclaimer: All product information and applications contained in this page may be subject to change without notice.