

PAYAK R404 A/T

PAYAK R406

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG		
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R404	50	265/50R20	107	T	-	BSW	8.5	8.0 - 9.0	774	277	9.6	975	2150	-	-	44	300	540	A	B
	55	275/55R20 XL	117	T	-	BSW	8.5	8.0 - 9.0	810	284	9.6	1285	2835	-	-	50	340	540	A	B
		285/55R20	115	T	-	BSW	9.0	8.5 - 9.5	822	297	9.6	1215	2680	-	-	44	300	540	A	B
	60	265/60R18	110	T	-	BSW	8.0	7.5 - 8.5	775	272	9.6	1060	2335	-	-	44	300	540	A	B
		275/60R20	115	T	-	BSW	8.0	7.5 - 8.5	838	279	9.6	1215	2680	-	-	44	300	540	A	B
	65	245/65R17	107	T	-	BSW	7.0	6.5 - 7.5	750	248	9.6	975	2150	-	-	44	300	540	A	B
		265/65R17	112	T	-	BSW	8.0	7.5 - 8.5	776	272	9.6	1120	2470	-	-	44	300	540	A	B
		275/65R18	116	T	-	BSW	8.0	7.5 - 8.5	815	279	9.6	1250	2755	-	-	44	300	540	A	B
	70	LT265/70R17	121/118	S	10	BSW/OWL	8.0	7.5 - 8.5	804	272	12.0	1450	3195	1320	2910	80	550	-	-	-
		LT285/70R17	121/118	S	10	BSW/OWL	8.5	8.0 - 9.0	832	292	9.6	1450	3195	1320	2910	80	550	-	-	-
		235/70R16	106	T	-	BSW/OWL	7.0	6.5 - 7.5	736	240	9.6	950	2095	-	-	44	300	540	A	B
		245/70R16 XL	111	T	-	BSW	7.0	6.5 - 7.5	750	248	9.6	1090	2405	-	-	50	340	540	A	B
		245/70R17	110	T	-	BSW/OWL	7.0	6.5 - 7.5	776	248	9.6	1060	2335	-	-	44	300	540	A	B
		255/70R16	111	T	-	BSW/OWL	7.5	7.0 - 8.0	764	260	9.6	1090	2405	-	-	44	300	540	A	B
		265/70R16	112	T	-	BSW/OWL	8.0	7.5 - 8.5	778	272	9.6	1120	2470	-	-	44	300	540	A	B
		265/70R17	115	T	-	BSW/OWL	8.0	7.5 - 8.5	804	272	9.6	1215	2680	-	-	44	300	540	A	B
		265/70R18	116	T	-	BSW	8.0	7.5 - 8.5	829	272	9.6	1250	2755	-	-	44	300	540	A	B
		285/70R17	117	T	-	BSW/OWL	8.5	9.0 - 10.0	832	292	9.6	1285	2835	-	-	44	300	540	A	B
	75	LT225/75R16	115/112	S	10	BSW/OWL	6.0	5.5 - 6.5	744	223	11.0	1215	2680	1120	2470	80	550	-	-	-
		LT235/75R15	104/101	S	6	BSW/OWL	6.5	6.0 - 7.0	733	235	11.0	900	1985	825	1820	50	350	-	-	-
		LT245/75R16	120/116	S	10	BSW/OWL	7.0	6.5 - 7.5	774	248	12.0	1400	3085	1250	2755	80	550	-	-	-
		LT245/75R17	121/118	S	10	BSW	7.0	6.5 - 7.5	800	248	12.1	1450	3195	1320	2910	80	550	-	-	-
		LT265/75R16	123/120	S	10	BSW/OWL	7.5	7.0 - 8.0	804	267	12.0	1550	3415	1400	3085	80	550	-	-	-
		LT285/75R16	126/123	S	10	BSW/OWL	8.0	7.5 - 8.5	834	286	12.1	1700	3750	1550	3415	80	550	-	-	-
		235/75R15	105	T	-	BSW/OWL	6.5	6.0 - 7.0	733	235	9.6	925	2040	-	-	44	300	540	A	B
		245/75R16	111	T	-	BSW/OWL	7.0	6.5 - 7.5	774	248	9.6	1090	2405	-	-	44	300	540	A	B
	80	265/75R16	116	T	-	BSW/OWL	7.5	7.0 - 8.0	804	267	9.6	1250	2755	-	-	44	300	540	A	B
		LT235/80R17	120/117	S	10	BSW	6.5	6.0 - 7.0	808	235	12.1	1400	3085	1285	2835	80	550	-	-	-
		LT215/85R16	115/112	S	10	BSW/OWL	6.0	5.5 - 6.5	772	216	11.0	1215	2680	1120	2470	80	550	-	-	-
	85	LT235/85R16	120/116	S	10	BSW/OWL	6.5	6.0 - 7.0	806	235	12.0	1400	3085	1250	2755	80	550	-	-	-
		30X9.50R15 LT	104	S	6	BSW/OWL	7.5	7.0 - 8.0	750	240	12.0	900	1985	-	-	50	350	-	-	-
	-	31X10.50R15 LT	109	S	6	BSW/OWL	8.5	8.0 - 9.0	775	268	12.0	1030	2270	-	-	50	350	-	-	-
	-	35X12.50R17 LT	121	S	10	BSW	10.0	9.5 - 10.5	877	318	12.0	1450	3195	-	-	65	450	-	-	-
R406	-	5.50R13 LT	97/95	P	12	BSW	4.0	3.5 - 4.5	622	151	8.9	730	1610	690	1520	91	625	-	-	-
	-	5.00R12 LT	88/86	P	10	BSW	3.5	3.0 - 4.0	568	134	8.9	560	1230	530	1160	73	500	-	-	-
	-	5.50R12 LT	92/90	P	10	BSW	3.5	3.0 - 4.0	600	160	8.5	630	1390	530	1320	73	500	-	-	-

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.