

PAYAK 007 R601

PAYAK H/T R602

PATTERN NAME	SERIES	SIZES	LI	SS	PR	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		MAX. LOAD CAPACITY DUAL		INFLATION PRESSURE		UTQG			
							STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.	
R601	50	265/50R20	107	V		BSW	8.5	8.0 - 9.0	774	277	8.4	975	2150			44	300	560	A	A	
		285/50R20	112	V	-	BSW	9.0	8.5 - 9.5	794	297	8.4	1120	2470	-	-	44	300	560	A	A	
		225/55R17 XL	101	H	-	BSW	7.0	6.5 - 7.5	680	233	8.4	825	1820	-	-	50	340	560	A	A	
	55	235/55R18 XL	104	V	-	BSW	7.5	7.0 - 8.0	715	245	8.4	900	1985	-	-	50	340	560	A	A	
		255/55R18 XL	109	V	-	BSW	8.0	7.5 - 8.5	737	265	8.4	1030	2270	-	-	50	340	560	A	A	
		275/55R20 XL	117	V	-	BSW	8.5	8.0 - 9.0	810	284	8.4	1285	2835	-	-	50	340	560	A	A	
	60	225/55R18	98	V	-	BSW	7.0	6.5 - 7.5	705	233	8.4	750	1655	-	-	44	300	560	A	A	
		265/60R18	110	H	-	BSW	8.0	7.5 - 8.5	775	272	8.4	1060	2335	-	-	44	300	560	A	A	
		235/60R18 XL	107	V	-	BSW	7.0	6.5 - 7.5	739	240	8.4	975	2150	-	-	50	340	560	A	A	
		275/60R20	115	H	-	BSW	8.0	7.5 - 8.5	838	279	8.4	1215	2680	-	-	44	340	560	A	A	
		285/60R18	116	V	-	BSW	8.5	8.0 - 9.0	799	292	8.4	1250	2755	-	-	44	340	560	A	A	
		245/60R18	105	V	-	BSW	7.0	6.5 - 7.5	751	248	8.4	925	2040	-	-	44	340	560	A	A	
		225/60R18	100	H	-	BSW	6.5	6.0 - 7.0	727	228	8.4	800	1765	-	-	44	340	560	A	A	
		235/60R17	102	H	-	BSW	7.0	6.5 - 7.5	714	240	8.4	850	1875	-	-	44	340	560	A	A	
		225/60R17	99	H	-	BSW	6.5	6.0 - 7.0	702	228	8.4	775	1710	-	-	44	340	560	A	A	
		225/65R17	102	H	-	BSW	6.5	6.0 - 7.0	724	228	8.4	850	1875	-	-	44	300	560	A	A	
		235/65R17 XL	108	H	-	BSW	7.0	6.5 - 7.5	738	240	8.4	1000	2205	-	-	50	340	560	A	A	
		65	245/65R17 XL	111	H	-	BSW	7.0	6.5 - 7.5	750	248	8.4	1090	2405	-	-	50	340	560	A	A
	265/65R17		112	H	-	BSW/OWL	8.0	7.5 - 8.5	776	272	8.4	1120	2470	-	-	44	300	560	A	A	
	275/65R18		116	H	-	BSW	8.0	7.5 - 8.5	815	279	8.4	1250	2755	-	-	44	300	560	A	A	
	215/65R16 XL		102	H	-	BSW	6.5	6.0 - 7.0	686	221	8.4	850	1875	-	-	50	340	560	A	A	
	255/65R18		111	H	-	BSW	7.5	7.0 - 8.0	789	260	8.4	1090	2405	-	-	44	340	560	A	A	
	285/65R17		116	H	-	BSW	8.5	8.0 - 9.0	802	292	8.4	1250	2755	-	-	44	340	560	A	A	
	70	205/70R14 XL	98	H	-	BSW	6.0	5.5 - 6.5	644	209	8.2	750	1655	-	-	50	340	560	A	A	
		205/70R15	96	H	-	BSW	6.0	5.5 - 6.5	669	209	8.2	710	1565	-	-	44	300	560	A	A	
		215/70R15	98	H	-	BSW	6.5	6.0 - 7.0	683	221	8.2	750	1655	-	-	44	300	560	A	A	
		215/70R16	100	H	-	BSW	6.5	6.0 - 7.0	708	221	8.4	800	1765	-	-	44	300	560	A	A	
		225/70R15	100	H	-	BSW	6.5	6.0 - 7.0	697	228	8.4	800	1765	-	-	44	300	560	A	A	
		225/70R16	103	H	-	BSW	6.5	6.0 - 7.0	722	228	8.4	875	1930	-	-	44	300	560	A	A	
		235/70R16	106	H	-	BSW	7.0	6.5 - 7.5	736	240	8.4	950	2095	-	-	44	300	560	A	A	
		235/70R17 XL	111	H	-	BSW	7.0	6.5 - 7.5	762	240	8.4	1090	2405	-	-	50	340	560	A	A	
		245/70R16 XL	111	H	-	BSW	7.0	6.5 - 7.5	750	248	8.4	1090	2405	-	-	50	340	560	A	A	
		245/70R17	110	H	-	BSW	7.0	6.5 - 7.5	776	248	8.4	1060	2335	-	-	44	300	560	A	A	
		265/70R16	112	H	-	BSW/OWL	8.0	7.5 - 8.5	778	272	8.4	1120	2470	-	-	44	300	560	A	A	
		265/70R17	115	H	-	BSW	8.0	7.5 - 8.5	804	272	8.4	1215	2680	-	-	44	300	560	A	A	
		265/70R18	116	H	-	BSW	8.0	7.5 - 8.5	829	272	8.4	1250	2755	-	-	44	300	560	A	A	
		255/70R18	113	H	-	BSW	7.5	7.0 - 8.0	815	260	8.4	1150	2535	-	-	44	300	560	A	A	
		255/70R16	111	H	-	BSW	7.5	7.0 - 8.0	764	260	8.4	1090	2405	-	-	44	300	560	A	A	
		235/70R15	103	H	-	BSW	7.0	6.5 - 7.5	711	240	8.4	875	1930	-	-	44	300	560	A	A	
		75	235/75R15 XL	109	T	-	BSW	6.5	6.0 - 7.0	733	235	8.4	1030	2270	-	-	50	340	560	A	A
			225/75R15	102	T	-	BSW	6.0	5.5 - 6.5	719	223	8.4	850	1875	-	-	44	300	560	A	A
	265/75R16		116	T	-	BSW	7.5	7.0 - 8.0	804	267	8.4	1250	2755	-	-	44	300	560	A	A	
245/75R16	111		T	-	BSW	7.0	6.5 - 7.5	774	248	8.4	1090	2405	-	-	44	300	560	A	A		
225/75R16 XL	108		T	-	BSW	6.0	5.5 - 6.5	744	223	8.4	1000	2205	-	-	50	340	560	A	A		
215/75R15	100		T	-	BSW	6.0	5.5 - 6.5	703	216	8.4	800	1765	-	-	44	300	560	A	A		
R602	60	285/60R18	116	H	-	BSW	8.5	8.0 - 9.0	799	292	10.0	1250	2755	-	-	44	300	560	A	A	
	65	285/65R17	116	H	-	BSW	8.5	8.0 - 9.0	802	292	10.0	1250	2755	-	-	44	300	560	A	A	
		275/65R17	115	T	-	BSW	8.0	7.5 - 8.5	790	279	10.0	1215	2680	-	-	44	300	560	A	A	
		70	275/70R16	114	T	-	BSW	8.0	7.5 - 8.5	792	279	10.0	1180	2600	-	-	44	300	560	A	A

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.