



PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
R702	30	225/30ZR20 XL	85	W	BSW	8.0	7.5 - 8.5	644	230	7.9	515	1140	50	340	500	A	A
		235/30ZR22 XL	90	W	BSW	8.5	8.0 - 9.0	701	242	8.0	600	1320	50	340	500	A	A
		245/30ZR22 XL	92	W	BSW	8.5	8.0 - 9.0	707	248	8.0	630	1390	50	340	500	A	A
		245/35ZR20 XL	95	W	BSW	8.5	8.0 - 9.0	680	248	7.9	690	1520	50	340	500	A	A
	35	255/35ZR20 XL	97	W	BSW	9.0	8.5 - 9.5	686	260	8.0	730	1610	50	340	500	A	A
		265/35R18 XL	97	W	BSW	9.5	9.0 - 10.0	643	271	8.0	730	1610	50	340	500	A	A
	40	245/40ZR18 XL	97	W	BSW	8.5	8.0 - 9.0	653	248	7.9	730	1610	50	340	500	A	A
		205/40ZR17 XL	84	W	BSW	7.5	7.0 - 8.0	596	212	7.9	500	1100	50	340	500	A	A
		275/40ZR20 XL	106	W	BSW	9.5	9.0 - 10.0	728	278	8.0	950	2095	50	340	500	A	A
	45	235/45ZR17 XL	97	W	BSW	8.0	7.5 - 8.5	644	236	7.9	730	1610	50	340	500	A	A
		225/45ZR18 XL	95	W	BSW	7.5	7.0 - 8.0	659	225	7.9	690	1520	50	340	500	A	A
		245/45ZR18 XL	100	W	BSW	8.0	7.5 - 8.5	677	243	7.9	800	1765	50	340	500	A	A
		245/45ZR17 XL	99	W	BSW	8.0	7.5 - 8.5	652	243	7.9	775	1710	50	340	500	A	A
		235/45ZR18 XL	98	W	BSW	8.0	7.5 - 8.5	669	236	7.9	750	1655	50	340	500	A	A
		205/45ZR16 XL	87	W	BSW	7.0	6.5 - 7.5	590	206	7.9	545	1200	50	340	500	A	A
		205/45ZR17 XL	88	W	BSW	7.0	6.5 - 7.5	616	206	7.9	560	1234	50	340	500	A	A
		215/45ZR17	87	W	BSW	7.0	6.5 - 7.5	626	213	7.9	545	1200	44	300	500	A	A
	50	245/45ZR20 XL	103	W	BSW	8.5	8.0 - 9.0	728	243	8.0	875	1930	50	340	500	A	A
		205/50R17	89	V	BSW	6.5	6.0 - 7.0	638	214	7.9	580	1280	44	300	500	A	A
		195/50R15	82	V	BSW	6.0	5.5 - 6.5	577	201	7.9	475	1050	44	300	500	A	A
		265/50R20 XL	111	V	BSW	8.5	8.0 - 9.0	774	277	8.6	1090	2405	50	340	500	A	A
	55	205/50ZR16	87	W	BSW	6.5	6.0 - 7.0	612	214	7.9	545	1200	44	300	500	A	A
		225/55ZR17	97	W	BSW	7.0	6.5 - 7.5	680	233	7.9	730	1610	44	300	500	A	A
		215/55ZR17 XL	98	W	BSW	7.0	6.5 - 7.5	668	226	7.9	750	1655	50	340	500	A	A
		235/55R17	99	H	BSW	7.5	7.0 - 8.0	690	245	7.9	775	1710	44	300	500	A	A
		235/55R19	101	V	BSW	7.5	7.0 - 8.0	741	245	7.9	825	1820	44	300	500	A	A
R203	55	185/55R15	82	V	BSW	6.0	5.5 - 6.5	585	194	7.8	475	1050	44	300	540	A	A
		165/55R14	72	H	BSW	5.0	4.5 - 5.5	538	170	7.8	355	785	44	300	540	A	A
	60	175/60R13	77	H	BSW	5.0	4.5 - 5.5	540	177	7.8	412	910	44	300	540	A	A
		175/60R15	81	H	BSW	5.0	4.5 - 5.5	591	177	7.8	462	1020	44	300	540	A	A
		205/60R14	88	H	BSW	6.0	5.5 - 6.5	602	209	7.8	560	1230	44	300	540	A	A
		185/60R15	84	H	BSW	5.5	5.0 - 6.0	603	189	7.8	500	1100	44	300	540	A	A
		185/60R14	82	H	BSW	5.5	5.0 - 6.0	578	189	7.8	475	1050	44	300	540	A	A
		165/60R13	73	H	BSW	5.0	4.5 - 5.5	528	170	7.8	365	800	44	300	540	A	A
	65	165/65R14	79	T	BSW	5.0	4.5 - 5.5	570	170	7.8	437	965	44	300	540	A	A
		175/65R14	82	H	BSW	5.0	4.5 - 5.5	584	177	7.8	475	1050	44	300	540	A	A
		175/65R15	84	H	BSW	5.0	4.5 - 5.5	609	177	7.8	500	1100	44	300	540	A	A
		185/65R14	86	H	BSW	5.5	5.0 - 6.0	596	189	7.8	530	1160	44	300	540	A	A
		185/65R15	88	H	BSW	5.5	5.0 - 6.0	621	189	7.8	560	1230	44	300	540	A	A
		165/65R13	77	T	BSW	5.0	4.5 - 5.5	544	170	7.8	412	910	44	300	540	A	A
		165/70R14	81	H	BSW	5.0	4.5 - 5.5	588	170	7.8	462	1020	44	300	540	A	A
	70	175/70R13	82	H	BSW	5.0	4.5 - 5.5	576	177	7.8	475	1050	44	300	540	A	A
		175/70R14	84	H	BSW	5.0	4.5 - 5.5	602	177	7.8	500	1100	44	300	540	A	A
		185/70R14	88	H	BSW	5.5	5.0 - 6.0	616	189	7.8	560	1230	44	300	540	A	A
		195/70R14	91	H	BSW	6.0	5.5 - 6.5	630	201	7.8	615	1355	44	300	540	A	A
		185/70R13	86	H	BSW	5.5	5.0 - 6.0	590	189	7.8	530	1160	44	300	540	A	A

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

RADIAL CATALOG