



PATTERN NAME	SERIES	SIZES	LI	SS	SIDE WALL	RIM WIDTH		OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	TREAD DEPTH (MM)	MAX. LOAD CAPACITY SINGLE		INFLATION PRESSURE		UTQG		
						STANDARD (INCH)	APPROVAL (INCH)				(KG)	(LBS)	(PSI)	(kPa)	TREAD.	TRAC.	TEMP.
RA801E	30	255/30ZR19 XL 91	Y	BSW	9.0	8.5 - 9.5	635	256	7.6	615	1355	50	340	300	AA	A	
		275/30ZR19 XL 96	Y	BSW	9.5	9.0 - 10.0	646	274	7.6	710	1565	50	340	300	AA	A	
	35	235/35ZR19 XL 91	Y	BSW	8.5	8.0 - 9.0	645	237	7.6	615	1355	50	340	300	AA	A	
		245/35ZR18 XL 92	Y	BSW	8.5	8.0 - 9.0	626	244	7.6	630	1390	50	340	300	AA	A	
		245/35ZR19 XL 93	Y	BSW	8.5	8.0 - 9.0	652	244	7.6	650	1435	50	340	300	AA	A	
		255/35ZR18 XL 94	Y	BSW	9.0	8.5 - 9.5	633	256	7.6	670	1480	50	340	300	AA	A	
		255/35ZR19 XL 96	Y	BSW	9.0	8.5 - 9.5	659	256	7.6	710	1565	50	340	300	AA	A	
		255/35ZR20 XL 97	Y	BSW	9.0	8.5 - 9.5	684	256	7.6	730	1610	50	340	300	AA	A	
		265/35ZR18 XL 97	Y	BSW	9.5	9.0 - 10.0	640	267	7.6	730	1610	50	340	300	AA	A	
		275/35ZR20 XL 102	Y	BSW	9.5	9.0 - 10.0	698	274	7.6	850	1875	50	340	300	AA	A	
		315/35ZR20 XL 110	W	BSW	11.0	10.5 - 11.5	728	320	7.6	1060	2335	50	340	300	AA	A	
		40	205/40ZR17 XL 84	W	BSW	7.5	7.0 - 8.0	594	209	7.6	500	1100	50	340	300	AA	A
	215/40ZR17 XL 87		W	BSW	7.5	7.0 - 8.0	601	215	7.6	545	1200	50	340	300	AA	A	
	215/40ZR18 XL 89		Y	BSW	7.5	7.0 - 8.0	626	215	7.6	580	1280	50	340	300	AA	A	
	225/40ZR18 XL 92		Y	BSW	8.0	7.5 - 8.5	637	230	7.6	630	1390	50	340	300	AA	A	
	235/40ZR18 XL 95		Y	BSW	8.5	8.0 - 9.0	642	237	7.6	690	1520	50	340	300	AA	A	
	235/40ZR19 XL 96		Y	BSW	8.5	8.0 - 9.0	668	237	7.6	710	1565	50	340	300	AA	A	
	245/40ZR17 XL 95		W	BSW	8.5	8.0 - 9.0	628	248	7.6	690	1520	50	340	300	AA	A	
	245/40ZR18 XL 97		Y	BSW	8.5	8.0 - 9.0	650	244	7.6	730	1610	50	340	300	AA	A	
	245/40ZR19 XL 98		Y	BSW	8.5	8.0 - 9.0	676	244	7.6	750	1655	50	340	300	AA	A	
	245/40ZR20 XL 99		Y	BSW	8.5	8.0 - 9.0	701	244	7.6	775	1710	50	340	300	AA	A	
	255/40ZR19 XL 100		Y	BSW	9.0	8.5 - 9.5	684	256	7.6	800	1765	50	340	300	AA	A	
	275/40ZR20 XL 106		Y	BSW	9.5	9.0 - 10.0	728	278	7.6	950	2095	50	340	300	AA	A	
	45	195/45ZR16 XL 84	W	BSW	6.5	6.0 - 7.0	582	195	7.6	500	1100	50	340	300	AA	A	
		205/45ZR16 XL 87	W	BSW	7.0	6.5 - 7.5	588	203	7.6	545	1200	50	340	300	AA	A	
		205/45ZR17 XL 88	W	BSW	7.0	6.5 - 7.5	614	203	7.6	560	1230	50	340	300	AA	A	
		215/45ZR16 XL 90	W	BSW	7.0	6.5 - 7.5	597	210	7.6	600	1320	50	340	300	AA	A	
		215/45ZR17 XL 91	W	BSW	7.0	6.5 - 7.5	623	210	7.6	615	1355	50	340	300	AA	A	
		225/45ZR17 XL 94	W	BSW	7.5	7.0 - 8.0	634	225	7.6	670	1480	50	340	300	AA	A	
		225/45ZR18 XL 95	Y	BSW	7.5	7.0 - 8.0	656	222	7.6	690	1520	50	340	300	AA	A	
		235/45ZR17 XL 97	W	BSW	8.0	7.5 - 8.5	644	236	7.6	730	1610	50	340	300	AA	A	
		235/45ZR18 XL 98	Y	BSW	8.0	7.5 - 8.5	666	232	7.6	750	1655	50	340	300	AA	A	
		235/45ZR19 XL 99	Y	BSW	8.0	7.5 - 8.5	691	232	7.6	775	1710	50	340	300	AA	A	
245/45ZR17 XL 99		W	BSW	8.0	7.5 - 8.5	649	239	7.6	775	1710	50	340	300	AA	A		
245/45ZR18 XL 100		Y	BSW	8.0	7.5 - 8.5	677	243	7.6	800	1765	50	340	300	AA	A		
245/45ZR19 XL 102	Y	BSW	8.0	7.5 - 8.5	700	239	7.6	850	1875	50	340	300	AA	A			
50	205/50ZR17 XL 93	W	BSW	6.5	6.0 - 7.0	638	214	7.6	650	1435	50	340	300	AA	A		
	215/50ZR17 XL 95	W	BSW	7.0	6.5 - 7.5	648	226	7.6	690	1520	50	340	300	AA	A		
	225/50ZR17 XL 98	W	BSW	7.0	6.5 - 7.5	658	233	7.6	750	1655	50	340	300	AA	A		
	235/50ZR18 XL 101	Y	BSW	7.5	7.0 - 8.0	690	241	7.6	825	1820	50	340	300	AA	A		
55	195/55R16 XL 91	V	BSW	6.0	5.5 - 6.5	617	198	7.6	615	1355	50	340	300	AA	A		
	205/55ZR16 XL 94	W	BSW	6.5	6.0 - 7.0	632	214	7.6	670	1480	50	340	300	AA	A		
	215/55ZR16 XL 97	W	BSW	7.0	6.5 - 7.5	642	226	7.6	730	1610	50	340	300	AA	A		
	215/55ZR17 XL 98	W	BSW	7.0	6.5 - 7.5	668	226	7.6	750	1655	50	340	300	AA	A		
	225/55ZR17 XL 101	W	BSW	7.0	6.5 - 7.5	680	233	7.6	825	1820	50	340	300	AA	A		
	235/55ZR17 XL 103	Y	BSW	7.5	7.0 - 8.0	687	241	7.6	875	1930	50	340	300	AA	A		

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.