

OFF ROAD

Very heavy loads normally on poor or unimproved surfaces



- Combination of rib & lug pattern for high traction and superior resistance to irregular wear.
- 3 zigzag grooves for excellent grip performance on wet, dry or snowy roads.
- Advanced cut & chip compound for anti-abrasion and resistance to cutting and tearing.

SK421



Size	PR	Load Range	Service Description	TT/TL	Max. Single Load (kg/Lbs)	Max. Dual Load (kg/Lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm.)	Section Width (mm.)	Tread Depth (mm.)	Tread Depth (32nd.)
7.50R16LT	14	G	122/121L	TL	1510/3330	1450/3195	690/100	6.00	805	203	12.70	16.00
9.00R20	14	G	141/139K	TT	2575/5675	2430/5355	790/115	7.00	1,028	258	14.96	18.85
10.00R20	16	H	146/143K	TT	3000/6610	2725/6005	830/120	7.50	1,059	272	15.90	20.03
10.00R20	18	J	154/151K	TT	3750/8270	3450/7610	830/120	7.50	1,059	271	15.90	20.03
11.00R20	16	H	150/147K	TT	3350/7390	3075/6780	830/120	8.00	1,084	291	16.70	21.04
11R22.5	14	G	144/142L	TL	2800/6175	2650/5840	720/105	8.25	1,060	285	16.57	20.88
11R22.5	16	H	146/143L	TL	3000/6610	2725/6005	830/120	8.25	1,060	285	16.57	20.88
11R22.5	16	H	148/145L	TL	3150/6940	2900/6395	850/123	8.25	1,060	285	16.57	20.88
11R22.5	18	J	151/148K	TL	3450/7606	3150/6945	930/135	8.25	1,060	285	16.57	20.88
315/80R22.5	20	L	157/154L	TL	4120/9090	3750/8270	900/130	9.00	1,076	312	17.50	22.05
385/65R22.5	20	L	160K	TL	4500/9920	-	900/130	11.75	1,072	386	16.00	20.16
11R24.5	16	H	149/146L	TL	3250/7160	3000/6610	830/120	8.25	1,104	279	17.50	22.05
12R24.5	16	H	152/149K	TL	3550/7830	3250/7160	830/120	9.00	1,135	300	17.50	22.05
11.00R24	16	H	154/151K	TT	3750/8270	3450/7610	830/120	8.00	1,186	293	16.00	20.16

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.