

REGIONAL

Regional for Driver Position



- Block pattern and open shoulder design for excellent traction and superior resistance to irregular wear.
- Block & grooves design for excellent grip performance on wet, dry or snowy roads.
- Advanced compound & construction for loading performance and increased durability.
- Strengthened casing for multiple retreadability.

SS431



Size	PR	Load Range	Service Description	TT/TL	Max. Single Load (kg/Lbs)	Max. Dual Load (kg/Lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm.)	Section Width (mm.)	Tread Depth (mm.)	Tread Depth (32nd.)
11R22.5	14	G	144/142L	TL	2800/6175	2650/5840	720/105	8.25	1,054	279	23.50	29.61
11R22.5	16	H	148/145L	TL	3150/6940	2900/6395	850/123	8.25	1,054	279	23.50	29.61
11R22.5	16	H	146/143L	TL	3000/6610	2725/6005	830/120	8.25	1,054	279	23.50	29.61
11R22.5	18	J	151/148K	TL	3450/7606	3150/6945	930/135	8.25	1,068	286	23.00	29.61
11R24.5	14	G	146/143L	TL	3000/6610	2725/6005	720/105	8.25	1,097	275	23.80	29.98
11R24.5	16	H	149/146L	TL	3250/7160	3000/6610	830/120	8.25	1,097	275	23.80	29.98
285/75R24.5	14	G	144/141L	TL	2800/6175	2575/5675	760/110	8.25	1,050	283	20.50	25.83
295/75R22.5	14	G	144/141L	TL	2800/6175	2575/5675	760/110	9.00	1,014	298	20.50	25.83
295/80R22.5	16	H	150/147L	TL	3350/7390	3075/6780	830/120	9.00	1,052	298	23.50	29.61
295/80R22.5	18	J	152/149L	TL	3550/7830	3250/7160	900/130	9.00	1,052	298	23.50	29.61
315/80R22.5	18	J	154/151L	TL	3750/8270	3450/7610	830/120	9.00	1,082	314	23.80	29.98
315/80R22.5	20	L	158/150L	TL	4250/9370	3350/7390	900/130	9.00	1,082	314	23.80	29.98



- Block pattern with wide tread shoulder design for enhancement of handling, grip & traction performance.
- 3D sipe design for excellent grip and traction performance on wet, dry or snowy roads and resist irregular wear.
- Advanced compound & construction for loading performance and increased durability.
- Strengthened casing for multiple retreadability.

SS433



Size	PR	Load Range	Service Description	TT/TL	Max. Single Load (kg/Lbs)	Max. Dual Load (kg/Lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm.)	Section Width (mm.)	Tread Depth (mm.)	Tread Depth (32nd.)
295/80R22.5	16	H	152/148M	TL	3550/7830	3150/6940	850/123	9.00	1,063	306	20.00	25.18
315/80R22.5	18	J	156/150L (154/150M)	TL	4000/8820	3350/7390	850/123	9.00	1,089	318	20.50	25.83

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.

DEESTONE

MOVE THE WORLD