

REGIONAL

Regional for All Wheel Position



- 5 rib tread design with wide shoulder for excellent handling stability.
- 4 wide straight grooves for efficient water evacuation and breaking performance in wet and dry traction.
- Advanced compound with low heat generation for increased durability.
- Strengthened casing for multiple retreadability.

SV401



Size	PR	Load Range	Service Description	TT/TL	Max. Single Load (kg/Lbs)	Max. Dual Load (kg/Lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm.)	Section Width (mm.)	Tread Depth (mm.)	Tread Depth (32nd.)
10.00R20	16	H	146/143L	TT	3000/6610	2725/6005	830/120	7.50	1051	274	15.90	20.03
11.00R20	16	H	150/147K	TT	3350/7390	3075/6780	830/120	8.00	1095	298	16.00	20.16
10R22.5	14	G	141/139L	TL	2575/5675	2430/5355	790/115	7.50	1019	254	15.00	18.90
11R22.5	16	H	146/143M	TL	3000/6610	2725/6005	830/120	8.25	1051	275	16.00	20.16
11R22.5	16	H	148/145L	TL	3150/6940	2900/6395	850/123	8.25	1051	275	16.00	20.16
11R22.5	18	J	151/148K	TL	3450/7606	3150/6945	930/135	8.25	1051	279	16.00	20.16
12R22.5	16	H	150/147K	TL	3350/7390	3075/6780	830/120	9.00	1085	300	16.00	20.16
215/75R17.5	16	H	135/133J	TL	2180/4805	2060/4540	850/122	6.00	776	225	12.70	16.00
235/75R17.5	16	H	132/130L	TL	2000/4410	1900/4189	775/115	6.75	797	233	14.00	17.64
8R19.5	12	F	124/122L	TL	1600/3525	1500/3305	760/110	6.00	859	203	15.00	18.90
225/70R19.5	10	E	121/119L	TL	1450/3195	1360/3000	550/80	6.75	811	226	12.70	16.00
225/70R19.5	14	G	128/126M	TL	1800/3970	1700/3750	760/110	6.75	811	226	12.70	16.00
245/70R19.5	16	H	135/133L	TL	2180/4805	2060/4540	830/120	7.50	839	248	14.00	17.64
265/70R19.5	16	H	140/138L	TL	2500/5510	2360/5205	830/120	7.50	873	262	14.00	17.64
295/80R22.5	16	H	150/147M	TL	3350/7390	3075/6780	830/120	9.00	1055	290	16.70	21.04
295/80R22.5	16	H	152/148M	TL	3550/7830	3150/6940	860/125	9.00	1055	290	16.70	21.04
295/80R22.5	18	J	152/149M	TL	3550/7830	3250/7160	900/130	9.00	1055	290	16.70	21.04
315/80R22.5	18	J	154/151M	TL	3750/8270	3450/7610	830/120	9.00	1083	318	17.50	22.05
315/80R22.5	18	J	154/151J	TL	3750/8270	3450/7610	830/120	9.00	1083	318	17.50	22.05
315/80R22.5	20	L	158/150L	TL	3750/8270	4250/9370	900/130	9.00	1083	318	17.50	22.05

Source : Deestone

Disclaimer: All product information and applications contained in this page may be subject to change without notice.