

REGIONAL

Regional for All Wheel Position



- 5 rib tread design with wide shoulder for excellent handling stability.
- 4 wide straight grooves for efficient water evacuation and breaking performance in wet and dry traction.
- Advanced compound with low heat generation for increased durability.
- Strengthened casing for multiple retreadability.

SV402



Size	PR	Load Range	Service Description	TT/TL	Max. Single Load (kg/Lbs)	Max. Dual Load (kg/Lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm.)	Section Width (mm.)	Tread Depth (mm.)	Tread Depth (32nd.)
7.50R16LT	14	G	122/121L	TT	1510/3330	1450/3195	690/100	6.00	805	203	11.90	14.99
8.25R16LT	14	G	128/126L	TT	1800/3970	1700/3750	670/98	6.50	855	224	12.80	16.13
9.5R17.5	14	G	129/127J	TL	1850/4080	1750/3860	750/108	6.75	842	236	13.50	17.01
9.5R17.5	14	G	129/127L	TL	1850/4080	1750/3860	750/108	6.75	842	236	13.50	17.01
9.5R17.5	16	H	143/141J	TL	2725/6005	2575/5675	875/127	6.75	842	236	13.50	17.01
9.5R17.5	16	H	143/141L	TL	2725/6005	2575/5675	875/127	6.75	842	236	13.50	17.01



- Wider Tread.
- 5 rib tread design with wide shoulder for excellent handling stability.
- 4 wide straight grooves for efficient water evacuation and breaking performance in wet and dry traction.
- Advanced compound with low heat generation for increased durability.
- Strengthened casing for multiple retreadability.

SV402 PLUS



Size	PR	Load Range	Service Description	TT/TL	Max. Single Load (kg/Lbs)	Max. Dual Load (kg/Lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm.)	Section Width (mm.)	Tread Depth (mm.)	Tread Depth (32nd.)
7.50R16LT	14	G	122/121L	TL	1510/3330	1450/3195	690/100	6.00	805	215	12.70	16.00
7.50R16LT	14	G	122/121L	TT	1510/3330	1450/3195	690/100	6.00	805	215	12.70	16.00
7.50R16LT	16	H	126/122L	TT	1680/3705	1510/3330	760/110	6.00	805	215	12.70	16.00
8.25R16LT	16	H	128/126M	TT	1800/3970	1700/3750	675/98	6.50	854	234	12.00	15.25
9.5R17.5LT	16	H	143/141K	TL	2725/6005	2575/5675	875/127	6.50	842	240	12.00	15.25