



MAXAM

MS902

BACKHOE - INDUSTRIAL SERVICE

Modified R1 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Inf. P.	Position	L.C.C. (lbs/kg)		L.I.
				in	in.	32nds	psi		5 mph	25 mph	
				mm	mm	mm	KPa		10 kph	40 kph	
12.5/80-18	12	TL	9.00	38.8	13.4	26	58	-	7500	6000	143A8
				986	340	21	400		3400	2725	
	14	TL	9.00	38.8	13.4	26	62	-	8000	6400	145A8
				986	340	21	425		3650	2900	
15.5/80-24 (400/80-24)	12	TL	13.00	50.0	15.5	35	44	-	11550	8250	154A8
				1270	394	28	300		5220	3750	
	14	TL	13.00	50.0	15.5	35	51	-	12320	8800	156A8
				1270	394	28	350		5600	4000	
	16	TL	13.00	50.0	15.5	35	58	-	13510	9650	159A8
				1270	394	28	400		6100	4375	
16.5/85-24	12	TL	13.00	52.0	16.4	35	40	FREE	14700	10500	162A8
				6670	4750	DRIVE	10360	7400			
				1321	417		28	275	4700	3350	150A8
				52.0	16.4	35	48	FREE	15960	11400	165A8
	1321	417	28	330	DRIVE	11270	8050				
	14	TL	13.00	52.0	16.4	35	55	FREE	17220	12300	168A8
				7810	5600	DRIVE	12320	8800			
				1321	417		28	380	5600	4000	156A8
				54.9	15.2	35	33	FREE	12320	8800	156A8
	1394	386	28	225	DRIVE	8610	6150				
	10	TL	W13	54.9	15.2	35	33	FREE	12320	8800	156A8
				1394	386	28	225	DRIVE	8610	6150	
									3900	2800	144A8