



**MAXAM**

# MS906

**SKID STEER**

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Inf. P.	L.C.C. (lbs/kg)	
				in mm	in. mm	32nds mm	psi KPa	5 mph 10 kph	30 mph 50 kph
5.70-12	6	TL	4.50	22.4	5.7	18	60	1450	900
				569	145	14	415	660	410
23x8.50-12	6	TL	7JA	22.9	8.5	17	50	1820	1145
				583	214	13	340	825	515
	8	TL	7JA	22.9	8.5	17	65	2150	1355
				583	214	13	450	975	615
12	TL	7JA	22.9	8.5	17	75	2680	1690	
			583	214	13	515	1215	760	
27x8.50-15	8	TL	7JA	26.9	8.7	18	60	2910	1820
				682	221	14	415	1320	825
27x10-12	14	TL	8.00G	27.6	10.4	24	100	7800	5040
				701	254	19	690	3500	2250
7.00-15	6	TL	5.50	29.9	7.8	21	60	3180	2015
				760	198	16	415	1400	920
	8	TL	5.50	29.9	7.8	21	70	3640	2290
				760	198	16	480	1650	1030
31x15.50-15	8	TL	13LB	31.0	15.1	30	45	4400	2760
				787.0	384	23	310	2000	1250
				30.2	10.7	21	75	4710	2950
				768	271	16	515	2130	1330
10-16.5	10	TL	8.25	32.8	13.0	25	80	6320	4030
12-16.5	12	TL	9.75	834	331	20	550	2850	1830
				36.2	14.2	33	80	8540	5360
14-17.5	14	TL	10.50	920	360	26	550	3870	2430
				40.2	15.3	33	70	10060	6425
	16	TL	11.75	1020	389	26	480	4560	2915
				40.2	15.3	33	80	10880	6930
15-19.5	16	TL	11.75	1020	389	26	550.0	4935	3150

