



MAXAM


MS965

IMPLEMENT I1

Ribbed implement I1 pattern for high flotation and minimal soil disturbance.

- Extra wide tread design provides maximum flotation
- Deep undertread and reinforced shoulder for improved stubble resistance
- Special cut resistant compound
- Low rolling resistance

Applications



Size	PR	Type	Rim	O.D.		S.W		T.D.		Infl. P.		LI/SS	
				in	mm	in	mm	32nds	mm	psi	kPa		
10.0/80-12	10	TL	9.00	28.0	711.0	10.4	264.0	9	7	57	390	121A8	109A8
10.0/75-15.3	10	TL	9.00	29.9	759.0	10.8	274.0	11	9	57	390	123A8	111A8
	18	TL	9.00	29.9	759.0	10.8	274.0	11	9	102	700	135A8	123A8
11.5/80-15.3	10	TL	9.00	33.3	846.0	11.4	290.0	11	9	50	340	131A8	119A8
	14	TL	9.00	33.3	846.0	11.4	290.0	11	9	68	475	139A8	126A8
12.5/80-15.3	14	TL	9.00	35.0	889.0	12.1	307.0	11	9	62	430	142A8	129A8
15.0/55-17	10	TL	13.00	33.5	851.0	15.4	391.0	12	10	38	260	134A8	122A8
	14	TL	13.00	33.5	851.0	15.4	391.0	12	10	58	400	141A8	128A8
19.0/45-17	14	TL	16.00	34.1	866.0	18.9	480.0	15	12	40	275	144A8	131A8
500/50-17	10	TL	16.00	36.8	935.0	19.8	503.0	15	12	30	200	140A8	128A8
	14	TL	16.00	36.8	935.0	19.8	503.0	15	12	41	280	149A8	137A8
13.0/65-18	16	TL	11.00	35.0	889.0	13.2	335.0	14	11	71	490	144A8	131A8
15.0/70-18	12	TL	13.00	39.0	991.0	15.6	396.0	16	13	45	310	145A8	133A8
380/55R16.5	150A8/B	TL	12.00	33.4	848.0	14.7	373.0	12	10	73	500	150A8/B	

