



## MG113

- 5 rib tread design with wider shoulder for excellent handling stability
- 4 wide straight grooves for efficient water evacuation and breaking performance in wet and dry traction
- Advanced compound with low heat generation for increased durability.
- Strengthened casing for multiple retreadability.

| Size        | Type | RP | Load Index | Speed Symbol | O.D (mm) | S.W (mm) | NSD (mm) | Rim  | Max. Load (kg) |      | Max. Pressure (kPa) |
|-------------|------|----|------------|--------------|----------|----------|----------|------|----------------|------|---------------------|
|             |      |    |            |              |          |          |          |      | Single         | Dual |                     |
| 295/80R22.5 | TL   | 18 | 152/149    | L            | 1044     | 298      | 15.0     | 9.00 | 3550           | 3250 | 900                 |



## MG116

- Block pattern and open shoulder design for excellent traction and superior resistance to irregular wear
- Block & grooves design for excellent grip performance on wet, dry or snowy roads
- Advanced compound & construction for loading performance and increasing durability
- Strengthened casing for multiple retreadability

| Size        | Type | RP | Load Index | Speed Symbol | O.D (mm) | S.W (mm) | NSD (mm) | Rim  | Max. Load (kg) |      | Max. Pressure (kPa) |
|-------------|------|----|------------|--------------|----------|----------|----------|------|----------------|------|---------------------|
|             |      |    |            |              |          |          |          |      | Single         | Dual |                     |
| 295/80R22.5 | TL   | 18 | 152/149    | L            | 1044     | 298      | 18.0     | 9.00 | 3550           | 3250 | 900                 |



## MG118

- Special tread design for high traction on wet and muddy road
- Tough belt construction for smooth tread wear and longer mileage
- Special tread compound for high resistant tread cut

| Size        | Type | RP | Load Index | Speed Symbol | O.D (mm) | S.W (mm) | NSD (mm) | Rim  | Max. Load (kg) |      | Max. Pressure (kPa) |
|-------------|------|----|------------|--------------|----------|----------|----------|------|----------------|------|---------------------|
|             |      |    |            |              |          |          |          |      | Single         | Dual |                     |
| 295/80R22.5 | TL   | 18 | 152/149    | L            | 1050     | 298      | 22.0     | 9.00 | 3550           | 3250 | 900                 |