

AZ670

Benefits and Features

- Premium five-rib tread with various pitches to provide quiet and comfortable riding
- Stone ejection design reduces stone retention and casing penetration
- Computer aided casing design helps improve footprint for better mileage performance



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
11R22.5	G/14	144/142M	16.0	8.25	1054	279	2800	720	2650	720
11R22.5	H/16	148/145M	16.0	8.25	1054	279	3150	850	2900	850
12R22.5	H/16	150/147L	16.0	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	16.0	9.00	1085	300	3550	930	3250	930
255/70R22.5	H/16	140/137M	15.0	7.50	930	255	2500	830	2300	830
295/80R22.5	H/16	150/147M	16.0	9.00	1044	298	3350	830	3075	830
295/80R22.5	J/18	152/149M	16.0	9.00	1044	298	3550	900	3250	900

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.