

AZ676

Benefits and Features

- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure			
							Single		Dual	
							(kg)	(kPa)	(kg)	(kPa)
6.50R16	F/12	110/105L	9.5	5.50F	750	185	1060	670	925	670
7.00R16	G/14	118/114L	11.0	5.50F	775	200	1320	770	1180	770
7.50R16	G/14	122/118L	12.0	6.00G	805	215	1500	770	1320	770
8.25R16	H/16	128/124L	14.0	6.50H	855	235	1800	770	1600	770
9.00R20	H/16	144/142K	15.5	7.0	1019	259	2800	900	2650	900
8.25R20	H/16	139/137K	15.0	6.5	974	236	2430	930	2300	930
10.00R20	H/16	146/143K	16.0	7.5	1054	278	3000	830	2725	830
10.00R20	J/18	149/146J	16.0	7.5	1054	278	3250	930	3000	930
11.00R20	J/18	152/149K	16.0	8.0	1085	293	3550	930	3250	930
12.00R20	J/18	154/151K	17.5	8.5	1125	315	3750	830	3450	830
11R22.5	G/14	144/142M	16.8	8.25	1054	279	2800	720	2650	720
11R22.5	H/16	148/145M	16.8	8.25	1065	279	3150	850	2900	850



12R22.5	H/16	150/147L	16.0	9.00	1085	300	3350	830	3075	830
12R22.5	J/18	152/149L	16.0	9.00	1085	300	3550	930	3250	930
295/80R22.5	H/16	150/147M	16.0	9.00	1044	298	3350	830	3075	830
295/80R22.5	J/18	152/149L	16.0	9.00	1044	298	3550	900	3250	900
315/80R22.5	J/18	154/151M(156/150L)	16.0	9.00	1076	312	3750	830	3450	830

Source : Trazano

Disclaimer: All product information and applications contained in this page may be subject to change without notice.